

屋内照明器具特性	
品番 (品名)	SC429
光源	LDA3L-E17/C/W ×1 280.0 lm
管理番号	K0158274(0)DB1
BZ分類	BZ10

器具効率	84 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	49 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	35 %	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	3.5	2.5	1.8	1.3	3.2	2.2	1.6	1.2	2.5	1.7	1.3	9	1.8	1.3	9	6	2	
	中 0.6	0.8	4.2	3.1	2.4	1.9	3.7	2.8	2.2	1.7	2.9	2.2	1.7	1.3	2.2	1.7	1.3	1.0	3	
	否 0.56	1.0	4.7	3.6	2.9	2.4	4.2	3.3	2.6	2.1	3.3	2.6	2.1	1.7	2.5	1.9	1.5	1.2	5	
		1.25	5.1	4.1	3.4	2.9	4.6	3.7	3.1	2.6	3.6	3.0	2.5	2.0	2.7	2.2	1.8	1.5	7	
下方投影面積	cm ²	1.5	5.4	4.5	3.8	3.3	4.9	4.1	3.5	3.0	3.9	3.3	2.8	2.4	2.9	2.5	2.1	1.8	8	
等価発光面積	cm ²	2.0	5.9	5.1	4.5	3.9	5.3	4.6	4.0	3.6	4.2	3.7	3.2	2.9	3.2	2.8	2.5	2.2	1.1	
取付高さ	器具間隔最大限		2.5	6.2	5.5	4.9	4.4	5.6	5.0	4.5	4.0	4.5	4.0	3.6	3.2	3.5	3.1	2.8	2.5	1.3
	横方向 (A)	縦方向 (B)	3.0	6.4	5.8	5.2	4.8	5.8	5.3	4.8	4.3	4.7	4.3	3.9	3.5	3.6	3.3	3.0	2.7	1.5
Hm	0.00Hm	0.00Hm	4.0	6.8	6.2	5.7	5.3	6.1	5.7	5.2	4.9	5.0	4.6	4.3	4.0	3.9	3.6	3.3	3.1	1.8
			5.0	7.0	6.5	6.1	5.7	6.3	5.9	5.6	5.2	5.2	4.8	4.5	4.3	4.0	3.8	3.6	3.4	2.0
			7.0	7.2	6.8	6.5	6.2	6.6	6.3	6.0	5.7	5.4	5.1	4.9	4.7	4.3	4.1	3.9	3.7	2.3
			10.0	7.4	7.1	6.9	6.6	6.8	6.5	6.3	6.1	5.6	5.4	5.2	5.0	4.4	4.3	4.2	4.0	2.5

