

屋内照明器具特性	
品番 (品名)	X E D 3 2 0 0 L
光源	LED2700_70_500 ×1 500.0 l m
管理番号	K0166788 (1) DB 1
B Z 分類	B Z 3

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	6 3	5 2	4 5	4 0	6 1	5 1	4 5	4 0	5 9	5 0	4 4	4 0	5 7	4 9	4 4	4 0	3 8
			0 . 6	0 . 8	7 3	6 3	5 6	5 2	7 2	6 3	5 6	5 1	6 9	6 1	5 6	5 1	6 7	6 0	5 5	5 1	4 9
			0 . 5 6	1 . 0	8 0	7 1	6 4	6 0	7 8	7 0	6 4	5 9	7 6	6 9	6 3	5 9	7 3	6 7	6 3	5 9	5 7
			1 . 2 5	8 5	7 8	7 2	6 7	8 4	7 7	7 1	6 7	8 1	7 5	7 0	6 6	7 9	7 4	6 9	6 6	6 4	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 9	8 2	7 7	7 2	8 8	8 1	7 6	7 2	8 5	7 9	7 5	7 1	8 3	7 8	7 4	7 1	6 9	
			2 . 0	9 4	8 8	8 4	8 0	9 3	8 7	8 3	7 9	9 0	8 5	8 2	7 9	8 7	8 4	8 0	7 8	7 6	
			2 . 5	9 7	9 2	8 8	8 5	9 5	9 1	8 7	8 4	9 3	8 9	8 6	8 3	9 0	8 7	8 5	8 2	8 0	
取付 高さ	器具間隔最大限		3 . 0	9 9	9 5	9 1	8 8	9 7	9 4	9 0	8 8	9 5	9 2	8 9	8 6	9 3	9 0	8 7	8 5	8 3	
	横方向 (A)	縦方向 (B)	4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	8 9	8 7	
H m	1 . 2 1 H m	1 . 2 1 H m	5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9	
			7 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 2	
			1 0 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4	

