

屋内照明器具特性	
品番 (品名)	XAS3023V
光源	LED3500_70_660 ×1 660.0 l m
管理番号	K0170906 (1) DB 1
B Z 分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
上方光束		0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
下方光束		1 0 0 %		室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	8 5	8 0	7 6	7 3	8 5	7 9	7 6	7 3	8 3	7 9	7 6	7 3	8 2	7 8	7 5	7 3	7 2		
			0 . 6 3	0 . 8	9 1	8 6	8 2	8 0	9 0	8 5	8 2	8 0	8 9	8 5	8 2	8 0	8 7	8 4	8 1	7 9	7 8		
				1 . 0	9 4	9 0	8 7	8 4	9 4	8 9	8 6	8 4	9 2	8 8	8 6	8 4	9 1	8 7	8 5	8 3	8 2		
			0 . 5 6	1 . 2 5	9 7	9 3	9 0	8 8	9 6	9 3	9 0	8 8	9 5	9 2	8 9	8 7	9 3	9 1	8 8	8 7	8 5		
下方投影面積		c m ²		1 . 5	9 9	9 6	9 3	9 1	9 8	9 5	9 2	9 0	9 6	9 4	9 1	9 0	9 5	9 2	9 1	8 9	8 8		
				2 . 0	1 0 1	9 9	9 6	9 4	1 0 0	9 8	9 6	9 4	9 9	9 6	9 5	9 3	9 7	9 5	9 3	9 2	9 0		
取付 高さ	器具間隔最大限			2 . 5	1 0 3	1 0 0	9 8	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 7	9 5	9 4	9 2		
	横方向 (A) 縦方向 (B)			3 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 7	9 9	9 8	9 6	9 5	9 3		
H m	0 . 4 1 H m 0 . 4 1 H m			4 . 0	1 0 5	1 0 3	1 0 2	1 0 1	1 0 4	1 0 2	1 0 1	1 0 0	1 0 2	1 0 1	9 9	9 8	1 0 0	9 9	9 8	9 7	9 5		
				5 . 0	1 0 6	1 0 4	1 0 3	1 0 2	1 0 5	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 6		
				7 . 0	1 0 6	1 0 5	1 0 4	1 0 4	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 7		
				1 0 . 0	1 0 7	1 0 6	1 0 6	1 0 5	1 0 6	1 0 5	1 0 5	1 0 4	1 0 4	1 0 3	1 0 3	1 0 2	1 0 2	1 0 1	1 0 1	1 0 0	9 8		

