

屋内照明器具特性	
品番 (品名)	XAS3004N
光源	LED5000_70_640 ×1 640.0 lm
管理番号	K0170999 (0) D 1
BZ分類	BZ4/8.5/BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		11 %	室指数	照明率 (X0.01) ZCM																		
下方光束		89 %																				
保守率		良 中 否	0.67	0.6	58	47	39	34	56	46	39	34	53	44	38	33	50	42	36	32	30	
			0.63	0.8	68	57	50	45	66	56	49	44	62	54	48	43	59	52	46	42	39	
			0.56	1.0	74	65	58	52	72	63	57	52	68	61	55	51	64	58	53	49	46	
				1.25	80	71	65	60	78	70	64	59	73	67	61	57	69	64	59	56	52	
下方投影面積		cm ²	1.5	84	76	70	65	81	74	69	64	77	71	66	62	73	68	64	60	56		
等価発光面積		cm ²	2.0	89	82	77	72	86	80	75	71	82	77	73	69	77	73	70	67	62		
取付 高さ	器具間隔最大限		2.5	92	86	82	77	90	84	80	76	85	81	77	74	80	77	74	71	67		
	横方向 (A) 縦方向 (B)		3.0	94	89	85	81	92	87	83	80	87	83	80	77	82	79	77	74	69		
H m	1.25 H m	1.25 H m	4.0	97	93	89	86	94	91	87	85	90	87	84	81	85	83	80	78	73		
			5.0	99	95	92	89	96	93	90	88	91	89	86	84	87	85	83	81	76		
			7.0	100	98	96	93	98	96	94	92	93	91	90	88	89	87	86	84	79		
			10.0	102	100	98	97	100	98	96	95	95	93	92	91	90	89	88	87	81		

