

屋内照明器具特性

品番 (品名)	XLGD671	
光源	LED2700_70_250 x1	250.0 lm
管理番号	K0162313(0)DB1	
BZ分類	BZ2/0.7/BZ3/2.8/BZ4	

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	97%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	66	56	49	45	64	55	49	45	62	54	48	44	60	53	48	44	42
	中	0.63	0.8	74	65	58	54	73	64	58	54	70	63	57	53	68	61	56	53	51
	否	0.56	1.0	80	71	65	60	78	70	64	60	75	68	63	59	73	67	62	59	56
			1.25	84	77	71	66	83	76	70	66	80	74	69	65	77	72	68	64	62
下方投影面積	cm ²		1.5	88	80	75	70	86	79	74	70	83	77	73	69	80	75	71	68	65
	等価発光面積		2.0	92	86	81	77	90	85	80	76	87	82	78	75	84	80	77	74	71
取付高さ	器具間隔最大限		2.5	95	90	85	81	93	88	84	81	90	86	82	79	87	83	80	78	75
	横方向 (A)	縦方向 (B)	3.0	97	92	88	85	95	91	87	84	92	88	85	82	89	86	83	81	78
Hm	0.93Hm	0.86Hm	4.0	99	95	92	89	97	94	91	88	94	91	89	86	91	89	87	85	81
			5.0	101	98	95	92	99	96	93	91	96	93	91	89	93	91	89	87	84
			7.0	102	100	98	96	101	99	97	95	98	96	94	92	95	93	92	90	87
			10.0	104	102	100	99	102	101	99	98	99	98	96	95	96	95	94	93	89

