

屋内照明器具特性	
品番 (品名)	XL573PHFK
光源	LED3500_85_4520 ×1 4520.0 lm
管理番号	K0162374 (1) DB 1
BZ分類	BZ4

器具効率		99 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 99 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.81	0.6	59	47	39	34	57	46	39	34	55	45	39	34	53	44	38	34	32	
			0.77	0.8	69	58	50	45	67	57	50	45	65	56	49	45	62	55	49	44	42	
			0.68	1.0	75	65	58	53	74	65	58	53	71	63	57	52	69	62	56	52	50	
				1.25	81	72	66	60	80	71	65	60	77	70	64	60	74	68	63	59	57	
下方投影面積		cm ²	1.5	85	77	71	66	84	76	70	66	81	74	69	65	78	73	68	64	62		
等価発光面積		cm ²	2.0	91	84	78	74	89	83	78	74	86	81	77	73	84	79	75	72	70		
取付 高さ	器具間隔最大限		2.5	94	88	84	79	92	87	83	79	90	85	81	78	87	83	80	77	75		
	横方向 (A) 縦方向 (B)		3.0	96	91	87	83	95	90	86	83	92	88	85	82	89	86	83	81	78		
1.5m	1.84 m	1.84 m	4.0	99	95	92	89	98	94	91	88	95	92	89	87	92	90	88	86	83		
2	2.43	2.43	5.0	101	98	95	92	99	97	94	91	97	94	92	90	94	92	90	89	86		
2.5	2.96	2.96	7.0	103	101	98	96	102	99	97	95	99	97	95	94	97	95	94	92	90		
3	3.55	3.56	10.0	104	103	101	100	103	101	100	99	101	99	98	97	98	97	96	95	92		

