

屋内照明器具特性	
品番 (品名)	XL 5 7 4 W B F K
光源	LED3500_85_2310 ×1 2310.0 lm
管理番号	K0162572 (0) DR 1
B Z 分類	BZ2 / 1.8 / BZ3

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束		1 0 0 %																					
保守率		良 中 否	0 . 7 7	0 . 6	6 7	5 7	5 1	4 6	6 6	5 6	5 0	4 6	6 4	5 6	5 0	4 6	6 2	5 5	5 0	4 6	4 4		
			0 . 7 2	0 . 8	7 6	6 7	6 1	5 6	7 5	6 6	6 1	5 6	7 3	6 5	6 0	5 6	7 1	6 4	5 9	5 6	5 4		
			0 . 6 8	1 . 0	8 2	7 4	6 8	6 3	8 1	7 3	6 7	6 3	7 8	7 2	6 7	6 3	7 6	7 0	6 6	6 2	6 1		
				1 . 2 5	8 7	8 0	7 4	7 0	8 5	7 9	7 4	7 0	8 3	7 7	7 3	6 9	8 1	7 6	7 2	6 9	6 7		
下方投影面積		cm ²	1 . 5	9 0	8 4	7 9	7 4	8 9	8 3	7 8	7 4	8 6	8 1	7 7	7 4	8 4	8 0	7 6	7 3	7 1			
等価発光面積		cm ²	2 . 0	9 5	8 9	8 5	8 1	9 3	8 8	8 4	8 1	9 1	8 6	8 3	8 0	8 8	8 5	8 2	7 9	7 7			
取付 高さ	器具間隔最大限		2 . 5	9 7	9 3	8 9	8 6	9 6	9 2	8 8	8 5	9 3	9 0	8 7	8 4	9 1	8 8	8 5	8 3	8 1			
	横方向 (A)	縦方向 (B)	3 . 0	9 9	9 5	9 2	8 9	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 7	9 3	9 0	8 8	8 6	8 4			
1 . 5m	1 . 8 8 m	1 . 2 3 m	4 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 5	9 2	9 7	9 5	9 3	9 1	9 5	9 3	9 1	9 0	8 7			
2	2 . 5 4	1 . 6 1	5 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 7	9 5	9 3	9 2	8 9			
2 . 5	3 . 0 2	1 . 9 2	7 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2			
3	3 . 6 3	2 . 3	1 0 . 0	1 0 5	1 0 4	1 0 3	1 0 2	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	9 9	9 9	9 8	9 7	9 4			

