

屋内照明器具特性	
品番 (品名)	XL575PFFK
光源	LED3500_85_7400 ×1 7400.0 lm
管理番号	K0162372 (*) DB 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	5 8	4 6	3 8	3 3	5 6	4 5	3 8	3 3	5 4	4 4	3 7	3 3	5 2	4 3	3 7	3 2	3 1		
			0 . 7 7	6 8	5 7	4 9	4 3	6 6	5 6	4 9	4 3	6 4	5 5	4 8	4 3	6 1	5 3	4 7	4 3	4 1		
			1 . 0	7 4	6 4	5 7	5 1	7 3	6 3	5 6	5 1	7 0	6 2	5 5	5 1	6 7	6 0	5 5	5 0	4 8		
			0 . 6 8	1 . 2 5	8 0	7 1	6 4	5 9	7 9	7 0	6 4	5 8	7 6	6 8	6 3	5 8	7 3	6 7	6 2	5 8	5 5	
下方投影面積		cm ²	1 . 5	8 4	7 6	7 0	6 4	8 3	7 5	6 9	6 4	8 0	7 3	6 8	6 3	7 7	7 1	6 7	6 3	6 1		
等価発光面積		cm ²	2 . 0	9 0	8 3	7 7	7 3	8 8	8 2	7 7	7 2	8 5	8 0	7 5	7 1	8 3	7 8	7 4	7 1	6 8		
取付 高さ	器具間隔最大限		2 . 5	9 3	8 7	8 2	7 8	9 2	8 6	8 2	7 8	8 9	8 4	8 0	7 7	8 6	8 2	7 9	7 6	7 3		
	横方向 (A)	縦方向 (B)	3 . 0	9 6	9 1	8 6	8 2	9 4	8 9	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 5	8 2	8 0	7 7		
1 . 5m	1 . 8 7 m	1 . 8 7 m	4 . 0	9 9	9 5	9 1	8 8	9 7	9 4	9 0	8 7	9 5	9 1	8 9	8 6	9 2	8 9	8 7	8 5	8 2		
2	2 . 4 8	2 . 4 8	5 . 0	1 0 1	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 6	9 4	9 1	8 9	9 4	9 2	9 0	8 8	8 5		
2 . 5	3 . 0 2	3 . 0 2	7 . 0	1 0 3	1 0 0	9 8	9 6	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 6	9 5	9 3	9 2	8 9		
3	3 . 6 3	3 . 6 2	1 0 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 0	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2		

