

屋内照明器具特性

品番 (品名)	L G W8 5 2 2 5 B									
光源	LDC5 L - E17 / C / D / W / 2 ×1 360.0 l m									
管理番号	K0169009 (0) DR 1									
B Z 分類	B Z 1 0									

器具効率		5 9 %	反射率	天井	8 0 %					7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		5 %	室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 3	0 . 6	2 5	1 9	1 5	1 2	2 2	1 6	1 3	1 0	1 5	1 2	9	7	9	7	6	4	0		
			0 . 6	0 . 8	3 0	2 4	1 9	1 6	2 6	2 0	1 7	1 4	1 8	1 4	1 2	1 0	1 1	9	7	6	0		
			0 . 5 6	1 . 0	3 3	2 7	2 3	2 0	2 8	2 4	2 0	1 7	2 0	1 7	1 4	1 2	1 2	1 0	9	8	0		
				1 . 2 5	3 6	3 1	2 7	2 3	3 1	2 7	2 3	2 0	2 2	1 9	1 6	1 5	1 3	1 1	1 0	9	0		
下方投影面積		c m ²		1 . 5	3 8	3 3	2 9	2 6	3 3	2 9	2 6	2 3	2 3	2 0	1 8	1 6	1 4	1 3	1 1	1 0	1		
等価発光面積			c m ²	2 . 0	4 1	3 7	3 3	3 0	3 6	3 2	2 9	2 7	2 5	2 3	2 1	1 9	1 5	1 4	1 3	1 2	1		
取付 高さ	器具間隔最大限		2 . 5	4 3	3 9	3 6	3 3	3 7	3 4	3 2	2 9	2 6	2 4	2 3	2 1	1 6	1 5	1 4	1 3	1			
	横方向 (A) 縦方向 (B)		3 . 0	4 4	4 1	3 8	3 6	3 8	3 6	3 3	3 1	2 7	2 5	2 4	2 2	1 7	1 6	1 5	1 4	1			
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	4 6	4 3	4 1	3 9	4 0	3 8	3 6	3 4	2 9	2 7	2 6	2 4	1 8	1 7	1 6	1 5	2			
			5 . 0	4 7	4 5	4 3	4 1	4 1	3 9	3 7	3 6	2 9	2 8	2 7	2 6	1 8	1 7	1 7	1 6	2			
			7 . 0	4 8	4 7	4 5	4 3	4 2	4 1	3 9	3 8	3 0	2 9	2 8	2 7	1 9	1 8	1 8	1 7	2			
			1 0 . 0	4 9	4 8	4 7	4 6	4 3	4 2	4 1	4 0	3 1	3 0	3 0	2 9	2 0	1 9	1 9	1 8	3			

