

屋内照明器具特性	
品番 (品名)	L G B 5 7 6 8 2 K
光源	LDA13L - G / Z100E / S / W ×6 1520.0 l m
管理番号	K0168441 (0) DB 1
BZ分類	BZ5

器具効率		8 1 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		2 5 % 5 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	4 2	3 2	2 6	2 2	4 0	3 1	2 5	2 2	3 5	2 8	2 4	2 0	3 2	2 6	2 2	1 9	1 6	
			0 . 6 3	0 . 8	4 9	4 0	3 4	3 0	4 7	3 9	3 3	2 9	4 2	3 5	3 0	2 7	3 7	3 2	2 8	2 5	2 1	
			1 . 0	5 4	4 6	4 0	3 5	5 1	4 4	3 8	3 4	4 6	4 0	3 5	3 2	4 1	3 6	3 2	2 9	2 5		
			0 . 5 6	1 . 2 5	5 9	5 1	4 5	4 1	5 6	4 9	4 4	3 9	5 0	4 4	4 0	3 6	4 5	4 0	3 7	3 4	2 9	
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	6 2	5 5	4 9	4 5	5 9	5 2	4 7	4 3	5 3	4 8	4 4	4 0	4 7	4 3	4 0	3 7	3 1		
			2 . 0	6 6	6 0	5 5	5 1	6 3	5 8	5 3	4 9	5 7	5 2	4 9	4 6	5 1	4 7	4 4	4 2	3 6		
取付 高さ	器具間隔最大限		2 . 5	6 9	6 4	5 9	5 6	6 6	6 1	5 7	5 4	5 9	5 5	5 2	4 9	5 3	5 0	4 8	4 5	3 9		
	横方向 (A) 縦方向 (B)		3 . 0	7 1	6 6	6 2	5 9	6 8	6 3	6 0	5 7	6 1	5 8	5 5	5 2	5 5	5 2	5 0	4 8	4 1		
H m	1 . 2 2 H m	1 . 2 6 H m	4 . 0	7 3	7 0	6 6	6 4	7 0	6 7	6 4	6 1	6 3	6 1	5 8	5 6	5 7	5 5	5 3	5 1	4 4		
			5 . 0	7 5	7 2	6 9	6 7	7 1	6 9	6 6	6 4	6 5	6 2	6 0	5 9	5 8	5 7	5 5	5 3	4 6		
			7 . 0	7 7	7 4	7 2	7 0	7 3	7 1	6 9	6 7	6 6	6 5	6 3	6 2	6 0	5 9	5 7	5 6	4 8		
			1 0 . 0	7 8	7 7	7 5	7 3	7 5	7 3	7 2	7 0	6 8	6 7	6 5	6 4	6 1	6 0	5 9	5 9	5 0		

