

屋内照明器具特性	
品番 (品名)	L G W 5 1 7 1 5 B
光源	LLD4300V ×1 930.0 lm
管理番号	K0165624(0)DB1
BZ分類	BZ5

器具効率	68%	天井	80%				70%				50%				30%				0%				
	上方光束 3%		下方光束 65%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
				壁	10%				10%				10%				10%				0%		
床	10%				10%				10%				10%				0%						
室指数	照明率 (X0.01)																			ZCM			
保守率	良	0.63	0.6	0.6	0.56	0.6	3.7	2.9	2.4	2.0	3.6	2.9	2.3	2.0	3.5	2.8	2.3	2.0	3.3	2.7	2.3	1.9	1.8
	中	0.6	0.6	0.6	0.6	0.8	4.4	3.6	3.1	2.7	4.3	3.5	3.0	2.7	4.1	3.4	3.0	2.6	3.9	3.3	2.9	2.6	2.4
	否	0.56	0.56	0.56	0.56	1.0	4.8	4.1	3.6	3.2	4.7	4.0	3.5	3.1	4.5	3.9	3.4	3.1	4.3	3.8	3.4	3.0	2.9
	0.56	0.56	0.56	0.56	1.25	5.2	4.6	4.0	3.6	5.1	4.5	4.0	3.6	4.9	4.3	3.9	3.6	4.6	4.2	3.8	3.5	3.3	3.3
下方投影面積	c m ²		1.5	5.5	4.9	4.4	4.0	5.4	4.8	4.3	4.0	5.1	4.6	4.2	3.9	4.9	4.5	4.1	3.8	3.6	3.6	3.6	3.6
	等価発光面積		c m ²	2.0	5.9	5.4	4.9	4.6	5.8	5.3	4.9	4.5	5.5	5.1	4.7	4.4	5.3	4.9	4.6	4.3	4.1	4.1	4.1
取付高さ	器具間隔最大限		2.5	6.1	5.7	5.3	4.9	6.0	5.6	5.2	4.9	5.7	5.4	5.1	4.8	5.5	5.2	4.9	4.7	4.5	4.5	4.5	4.5
	H m	1.26 H m	1.26 H m	3.0	6.3	5.9	5.5	5.2	6.2	5.8	5.5	5.2	5.9	5.6	5.3	5.1	5.7	5.4	5.2	5.0	4.7	4.7	4.7
H m	1.26 H m	1.26 H m	4.0	6.5	6.2	5.9	5.6	6.4	6.1	5.8	5.6	6.1	5.9	5.6	5.4	5.9	5.7	5.5	5.3	5.1	5.1	5.1	5.1
			5.0	6.7	6.4	6.1	5.9	6.5	6.3	6.0	5.8	6.3	6.1	5.9	5.7	6.0	5.9	5.7	5.5	5.3	5.3	5.3	5.3
			7.0	6.8	6.6	6.4	6.2	6.7	6.5	6.3	6.1	6.5	6.3	6.1	6.0	6.2	6.1	6.0	5.8	5.6	5.6	5.6	5.6
			10.0	6.9	6.8	6.6	6.5	6.8	6.7	6.5	6.4	6.6	6.5	6.3	6.2	6.4	6.3	6.2	6.1	6.0	5.8	5.8	5.8

