

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XLGB82800                  |
| 光源       | LED5000_70_400 ×1 400.0 lm |
| 管理番号     | K0171431 ( 0 ) DB 1        |
| BZ分類     | BZ9 / 0.7 / BZ8            |

| 器具効率             |                     | 100 %                              | 反射率  | 天井                | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |
|------------------|---------------------|------------------------------------|------|-------------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|
|                  |                     |                                    |      | 壁                 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |
|                  |                     |                                    |      | 床                 | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |
| 上方光束<br>下方光束     |                     | 44 %<br>56 %                       | 室指数  | 照明率 ( X0.01 ) ZCM |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |
| 保守率              |                     | 良<br>中<br>否                        | 0.63 | 0.6               | 45   | 33 | 25 | 19 | 42   | 30 | 23 | 18 | 35   | 26 | 20 | 15 | 29   | 21 | 16 | 13 | 8   |  |
|                  |                     |                                    | 0.6  | 0.8               | 54   | 41 | 33 | 27 | 49   | 38 | 31 | 25 | 41   | 33 | 26 | 21 | 34   | 27 | 22 | 18 | 12  |  |
|                  |                     |                                    | 0.56 | 1.0               | 60   | 48 | 39 | 33 | 55   | 44 | 37 | 31 | 46   | 38 | 31 | 26 | 38   | 31 | 26 | 22 | 15  |  |
|                  |                     |                                    | 1.25 | 1.25              | 65   | 54 | 46 | 39 | 60   | 50 | 43 | 37 | 51   | 43 | 37 | 32 | 42   | 36 | 31 | 27 | 18  |  |
| 下方投影面積<br>等価発光面積 |                     | cm <sup>2</sup><br>cm <sup>2</sup> | 1.5  | 69                | 59   | 51 | 44 | 64 | 55   | 47 | 42 | 54 | 47   | 41 | 36 | 45 | 39   | 34 | 30 | 21 |     |  |
|                  |                     |                                    | 2.0  | 75                | 66   | 59 | 52 | 69 | 61   | 55 | 49 | 59 | 52   | 47 | 43 | 49 | 44   | 40 | 36 | 26 |     |  |
| 取付<br>高さ         | 器具間隔最大限             |                                    | 2.5  | 79                | 71   | 64 | 58 | 73 | 66   | 60 | 54 | 62 | 56   | 52 | 47 | 52 | 47   | 44 | 40 | 29 |     |  |
|                  | 横方向 ( A ) 縦方向 ( B ) |                                    | 3.0  | 81                | 74   | 68 | 63 | 76 | 69   | 64 | 59 | 64 | 59   | 55 | 51 | 54 | 50   | 47 | 43 | 32 |     |  |
| H m              | 1.61 H m            | 1.66 H m                           | 4.0  | 85                | 79   | 74 | 69 | 79 | 74   | 69 | 65 | 68 | 64   | 60 | 56 | 57 | 54   | 51 | 48 | 35 |     |  |
|                  |                     |                                    | 5.0  | 87                | 82   | 77 | 73 | 81 | 77   | 72 | 69 | 70 | 66   | 63 | 60 | 59 | 56   | 54 | 51 | 38 |     |  |
|                  |                     |                                    | 7.0  | 90                | 86   | 82 | 79 | 84 | 80   | 77 | 74 | 73 | 70   | 67 | 64 | 62 | 59   | 57 | 55 | 42 |     |  |
|                  |                     |                                    | 10.0 | 92                | 89   | 86 | 83 | 86 | 83   | 81 | 78 | 75 | 73   | 70 | 68 | 64 | 62   | 60 | 59 | 45 |     |  |

