

屋内照明器具特性	
品番 (品名)	XLGB82801
光源	LED3500_70_400 ×1 400.0 lm
管理番号	K0171431 (0) DB 1
BZ分類	BZ9 / 0.7 / BZ8

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束 下方光束		4 4 % 5 6 %	室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6	0 . 6	4 5	3 3	2 5	1 9	4 2	3 0	2 3	1 8	3 5	2 6	2 0	1 5	2 9	2 1	1 6	1 3	8
			0 . 6	0 . 8	5 4	4 1	3 3	2 7	4 9	3 8	3 1	2 5	4 1	3 3	2 6	2 1	3 4	2 7	2 2	1 8	1 2			
			0 . 5 6	1 . 0	6 0	4 8	3 9	3 3	5 5	4 4	3 7	3 1	4 6	3 8	3 1	2 6	3 8	3 1	2 6	2 2	1 5			
			1 . 2 5	6 5	5 4	4 6	3 9	6 0	5 0	4 3	3 7	5 1	4 3	3 7	3 2	4 2	3 6	3 1	2 7	1 8				
下方投影面積		c m ²	1 . 5	6 9	5 9	5 1	4 4	6 4	5 5	4 7	4 2	5 4	4 7	4 1	3 6	4 5	3 9	3 4	3 0	2 1				
等価発光面積			c m ²	2 . 0	7 5	6 6	5 9	5 2	6 9	6 1	5 5	4 9	5 9	5 2	4 7	4 3	4 9	4 4	4 0	3 6	2 6			
取付高さ	器具間隔最大限		2 . 5	7 9	7 1	6 4	5 8	7 3	6 6	6 0	5 4	6 2	5 6	5 2	4 7	5 2	4 7	4 4	4 0	2 9				
	横方向 (A) 縦方向 (B)		3 . 0	8 1	7 4	6 8	6 3	7 6	6 9	6 4	5 9	6 4	5 9	5 5	5 1	5 4	5 0	4 7	4 3	3 2				
H m	1 . 6 1 H m	1 . 6 6 H m	4 . 0	8 5	7 9	7 4	6 9	7 9	7 4	6 9	6 5	6 8	6 4	6 0	5 6	5 7	5 4	5 1	4 8	3 5				
			5 . 0	8 7	8 2	7 7	7 3	8 1	7 7	7 2	6 9	7 0	6 6	6 3	6 0	5 9	5 6	5 4	5 1	3 8				
			7 . 0	9 0	8 6	8 2	7 9	8 4	8 0	7 7	7 4	7 3	7 0	6 7	6 4	6 2	5 9	5 7	5 5	4 2				
			1 0 . 0	9 2	8 9	8 6	8 3	8 6	8 3	8 1	7 8	7 5	7 3	7 0	6 8	6 4	6 2	6 0	5 9	4 5				

