

| 屋内照明器具特性 |                            |
|----------|----------------------------|
| 品番 (品名)  | XLGB82820                  |
| 光源       | LED5000_70_140 ×1 140.0 lm |
| 管理番号     | K0169176 ( 0 ) DR 1        |
| BZ分類     | BZ3                        |

| 器具効率     |           | 100 %           | 反射率             | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |   |  |   |
|----------|-----------|-----------------|-----------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|---|--|---|
|          |           |                 |                 | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |   |  |   |
|          |           |                 |                 | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |   |  |   |
| 上方光束     |           | 29 %            | 室指数             | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | C |  | M |
| 下方光束     |           | 71 %            |                 |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |   |  |   |
| 保守率      |           | 良<br>中<br>否     | 0.63            | 0.6           | 57   | 46 | 39 | 34 | 54   | 44 | 38 | 34 | 49   | 41 | 36 | 32 | 45   | 38 | 34 | 30 | 27  |  |   |   |  |   |
|          |           |                 | 0.6             | 0.8           | 66   | 56 | 50 | 45 | 63   | 54 | 48 | 44 | 58   | 50 | 45 | 41 | 52   | 46 | 42 | 39 | 34  |  |   |   |  |   |
|          |           |                 | 0.56            | 1.0           | 73   | 64 | 57 | 52 | 69   | 61 | 55 | 51 | 63   | 56 | 52 | 48 | 57   | 52 | 48 | 45 | 40  |  |   |   |  |   |
|          |           |                 |                 | 1.25          | 78   | 70 | 64 | 59 | 75   | 67 | 62 | 57 | 68   | 62 | 58 | 54 | 62   | 57 | 54 | 51 | 45  |  |   |   |  |   |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5             | 82            | 74   | 69 | 64 | 78 | 72   | 66 | 62 | 71 | 66   | 62 | 58 | 65 | 61   | 57 | 55 | 48 |     |  |   |   |  |   |
| 等価発光面積   |           |                 | cm <sup>2</sup> | 2.0           | 87   | 81 | 76 | 72 | 83   | 77 | 73 | 69 | 75   | 71 | 68 | 65 | 69   | 65 | 63 | 60 | 53  |  |   |   |  |   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5             | 90            | 85   | 80 | 77 | 86 | 81   | 77 | 74 | 78 | 75   | 72 | 69 | 71 | 68   | 66 | 64 | 56 |     |  |   |   |  |   |
|          | 横方向 ( A ) |                 | 縦方向 ( B )       | 3.0           | 92   | 87 | 83 | 80 | 88   | 84 | 80 | 77 | 80   | 77 | 74 | 72 | 73   | 70 | 68 | 67 | 58  |  |   |   |  |   |
| H m      | 0.60 H m  | 1.22 H m        | 4.0             | 94            | 91   | 88 | 85 | 90 | 87   | 84 | 82 | 82 | 80   | 78 | 76 | 75 | 73   | 72 | 70 | 61 |     |  |   |   |  |   |
|          |           |                 | 5.0             | 96            | 93   | 90 | 88 | 92 | 89   | 87 | 85 | 84 | 82   | 80 | 78 | 76 | 75   | 73 | 72 | 63 |     |  |   |   |  |   |
|          |           |                 | 7.0             | 98            | 95   | 93 | 92 | 93 | 92   | 90 | 88 | 85 | 84   | 83 | 81 | 78 | 77   | 76 | 75 | 65 |     |  |   |   |  |   |
|          |           |                 | 10.0            | 99            | 97   | 96 | 95 | 95 | 93   | 92 | 91 | 87 | 86   | 85 | 84 | 79 | 78   | 78 | 77 | 67 |     |  |   |   |  |   |

