

屋内照明器具特性	
品番 (品名)	L S E B 3 2 4 3
光源	LED2700_70_326 ×1 326.0 l m
管理番号	K0150116 (0) DB 1
B Z 分類	BZ3 / 0.7 / BZ4 / 2.3 / BZ5

器具効率		100 % 上方光束 10 % 下方光束 90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
					床	10 %				10 %				10 %				10 %				0 %	
						室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	60	49	42	38	59	48	42	37	55	47	41	37	53	45	40	36	33		
			0.63	0.8	69	58	51	46	67	57	50	45	63	55	49	44	60	53	47	43	41		
			0.56	1.0	74	64	57	52	72	63	56	51	68	60	55	50	64	58	53	49	46		
			1.25	79	70	63	58	77	69	62	57	73	66	60	56	69	63	58	54	51			
下方投影面積		cm ²	1.5	83	75	68	63	81	73	67	62	76	70	65	60	72	67	62	59	55			
等価発光面積			cm ²	2.0	88	81	75	70	85	79	74	69	81	75	71	67	76	72	68	65	61		
				2.5	91	85	80	75	88	83	78	74	84	79	75	72	79	76	72	69	65		
取付 高さ	器具間隔最大限		3.0	93	88	83	79	91	86	81	78	86	82	78	75	82	78	75	72	68			
	横方向 (A)			縦方向 (B)		4.0	96	92	88	84	94	90	86	83	89	86	82	80	84	82	79	77	72
H m	1.22 H m		1.22 H m		5.0		98	94	91	88	95	92	89	86	91	88	85	83	86	84	82	80	75
			7.0	100			97	94	92	98	95	92	90	93	91	89	87	89	87	85	83	78	
				10.0			102	99	97	96	99	97	95	94	95	93	91	90	90	89	88	86	81

