

屋内照明器具特性	
品番 (品名)	X S L G 1 0 9 L S
光源	LED2700_70_185 ×1 185.0 l m
管理番号	K0169182 (1) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z C M															
保守率		良 中 否	0.63	0.6	51	40	33	28	47	37	31	26	40	32	27	23	33	28	24	21	16	
			0.6	0.8	60	50	43	37	56	47	40	36	47	40	35	32	40	35	31	28	21	
			0.56	1.0	66	57	50	45	62	53	47	42	52	46	41	38	44	40	36	33	25	
				1.25	72	63	57	52	67	59	54	49	57	51	47	44	48	44	41	38	29	
下方投影面積		c m ²	等価発光面積 <td>1.5</td> <td>76</td> <td>68</td> <td>62</td> <td>57</td> <td>70</td> <td>64</td> <td>58</td> <td>54</td> <td>60</td> <td>55</td> <td>51</td> <td>48</td> <td>51</td> <td>47</td> <td>44</td> <td>42</td> <td>32</td>	1.5	76	68	62	57	70	64	58	54	60	55	51	48	51	47	44	42	32	
等価発光面積				c m ²	2.0	81	75	69	65	75	70	65	61	64	60	57	54	54	51	49	47	36
取付高さ	器具間隔最大限				2.5	84	79	74	70	78	73	69	66	67	64	61	58	57	54	52	50	38
	横方向 (A)				縦方向 (B)		3.0	86	82	77	74	80	76	73	69	69	66	63	61	58	56	54
H m	0.00 H m	1.63 H m	4.0	89	85	82	79	83	80	77	74	71	69	67	65	60	59	57	56	42		
			5.0	91	88	85	82	84	82	79	77	73	71	69	67	61	60	59	58	44		
			7.0	93	90	88	86	86	84	83	81	74	73	72	70	63	62	61	60	45		
			10.0	94	92	91	89	88	86	85	84	76	75	74	73	64	63	63	62	46		

