

屋内照明器具特性	
品番 (品名)	X S L G 1 0 7 V S
光源	LED3500_70_215 ×1 215.0 l m
管理番号	K0169180 (1) DR 1
B Z 分類	BZ5 / 0.7 / BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 0	3 9	3 2	2 7	4 6	3 6	3 0	2 5	3 9	3 2	2 6	2 3	3 3	2 7	2 3	2 0	1 5
			0 . 6	0 . 8	6 0	4 9	4 2	3 7	5 5	4 6	3 9	3 5	4 7	4 0	3 5	3 1	3 9	3 4	3 0	2 7	2 0
				1 . 0	6 6	5 6	4 9	4 4	6 1	5 2	4 6	4 2	5 2	4 5	4 1	3 7	4 3	3 9	3 5	3 2	2 4
			0 . 5 6	1 . 2 5	7 1	6 3	5 6	5 1	6 6	5 9	5 3	4 8	5 6	5 1	4 6	4 3	4 7	4 3	4 0	3 7	2 8
下方投影面積		c m ²		1 . 5	7 5	6 7	6 1	5 6	7 0	6 3	5 7	5 3	5 9	5 4	5 0	4 7	5 0	4 6	4 3	4 1	3 1
			等価発光面積	c m ²	2 . 0	8 0	7 4	6 9	6 4	7 5	6 9	6 4	6 0	6 4	6 0	5 6	5 3	5 4	5 1	4 8	4 6
取付 高さ	器具間隔最大限			2 . 5	8 4	7 8	7 3	6 9	7 8	7 3	6 9	6 5	6 6	6 3	6 0	5 7	5 6	5 3	5 1	4 9	3 7
	横方向 (A) 縦方向 (B)			3 . 0	8 6	8 1	7 7	7 3	8 0	7 6	7 2	6 9	6 8	6 5	6 3	6 0	5 8	5 5	5 3	5 2	3 9
H m	0 . 0 0 H m	1 . 6 7 H m		4 . 0	8 9	8 5	8 1	7 8	8 3	7 9	7 6	7 4	7 1	6 8	6 6	6 4	6 0	5 8	5 6	5 5	4 1
				5 . 0	9 0	8 7	8 4	8 2	8 4	8 1	7 9	7 7	7 2	7 0	6 8	6 7	6 1	6 0	5 8	5 7	4 3
				7 . 0	9 2	9 0	8 8	8 6	8 6	8 4	8 2	8 0	7 4	7 2	7 1	7 0	6 2	6 1	6 0	5 9	4 4
				1 0 . 0	9 4	9 2	9 1	8 9	8 7	8 6	8 5	8 3	7 5	7 4	7 3	7 2	6 4	6 3	6 2	6 1	4 6

