

屋内照明器具特性	
品番 (品名)	NNN7 4 5 0 0 K
光源	NNU240115KLE9 ×1 1840.0 l m
管理番号	K0190844 (1) DB 1
B Z 分類	B Z 2

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		79 %	室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.77	0.6	54	46	42	38	53	46	41	38	52	45	41	38	50	45	41	38	37
			0.72	0.8	62	55	50	47	61	54	50	47	59	53	49	46	57	53	49	46	45
			0.68	1.0	66	60	56	53	65	60	56	52	64	59	55	52	62	58	55	52	51
				1.25	70	65	61	58	69	64	61	58	67	63	60	57	66	62	59	57	55
下方投影面積		cm ²	1.5	73	68	64	61	72	67	64	61	70	66	63	61	68	65	62	60	59	
等価発光面積			cm ²	2.0	76	72	69	67	75	72	69	66	73	70	68	66	72	69	67	65	63
取付 高さ	器具間隔最大限		2.5	78	75	72	70	77	74	72	70	75	73	71	69	73	71	70	68	66	
	横方向 (A) 縦方向 (B)		3.0	80	77	74	72	79	76	74	72	77	74	73	71	75	73	71	70	68	
H m	1.12 H m	1.12 H m	4.0	81	79	77	75	80	78	76	75	78	77	75	74	76	75	74	73	71	
			5.0	82	80	79	77	81	80	78	77	79	78	77	75	77	76	75	74	72	
			7.0	83	82	81	80	82	81	80	79	80	79	78	78	79	78	77	76	74	
			10.0	84	83	82	81	83	82	81	81	81	81	80	79	79	79	78	78	76	

