

屋内照明器具特性	
品番 (品名)	NNN7 4 5 0 0 K
光源	NNU140115KLE9 ×1 1020.0 l m
管理番号	K0190852 (1) DB 1
B Z 分類	B Z 2

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.77	0.6	54	46	41	38	53	46	41	38	51	45	41	38	50	44	41	38	36
			0.72	0.8	61	54	50	46	60	54	50	46	59	53	49	46	57	52	49	46	45
			0.68	1.0	66	60	56	52	65	59	55	52	63	58	55	52	62	57	54	52	50
			1.25	70	65	61	57	69	64	60	57	67	63	60	57	65	62	59	57	55	
下方投影面積 等価発光面積		cm ² cm ²	1.5	73	68	64	61	72	67	64	61	70	66	63	60	68	65	62	60	58	
			2.0	76	72	69	66	75	71	68	66	73	70	67	65	71	69	66	65	63	
			2.5	78	75	72	70	77	74	71	69	75	72	70	68	73	71	69	68	66	
取付 高さ	器具間隔最大限		3.0	79	76	74	72	78	76	73	71	76	74	72	70	74	73	71	70	68	
	横方向 (A)	縦方向 (B)	4.0	81	79	77	75	80	78	76	74	78	76	75	73	76	75	73	72	70	
H m	1.12 H m	1.12 H m	5.0	82	80	78	77	81	79	78	76	79	78	76	75	77	76	75	74	72	
			7.0	83	82	80	79	82	81	80	78	80	79	78	77	78	77	77	76	74	
			10.0	84	83	82	81	83	82	81	80	81	80	79	79	79	79	78	77	75	

