

屋内照明器具特性	
品番 (品名)	NNN7 4 5 0 0 K
光源	NNU141115KLE9 ×1 1020.0 l m
管理番号	K0190854 (1) DB 1
B Z 分類	BZ1 / 1.4 / BZ2 / 8.5 / BZ1

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.77	0.6	55	49	44	41	55	48	44	41	53	48	44	41	52	47	44	41	40
			0.72	0.8	62	56	52	49	61	55	51	48	59	54	51	48	58	54	51	48	47
			0.68	1.0	66	60	56	53	65	60	56	53	63	59	56	53	62	58	55	53	52
				1.25	69	64	61	58	68	64	60	58	67	63	60	57	65	62	59	57	56
下方投影面積		c m ²		1.5	71	67	64	61	70	67	63	61	69	65	63	60	67	64	62	60	59
			等価発光面積	c m ²	2.0	74	71	68	66	73	70	68	65	72	69	67	65	70	68	66	64
取付 高さ	器具間隔最大限			2.5	76	73	71	69	75	72	70	68	73	71	69	67	72	70	68	67	65
	横方向 (A) 縦方向 (B)			3.0	77	75	73	71	76	74	72	70	75	73	71	69	73	71	70	69	67
H m	0.76 H m 0.76 H m			4.0	79	77	75	73	78	76	74	73	76	74	73	72	74	73	72	71	69
				5.0	80	78	77	75	79	77	76	75	77	76	75	73	75	74	73	72	70
				7.0	81	79	78	77	80	79	78	77	78	77	76	75	76	75	75	74	72
				10.0	81	80	80	79	80	80	79	78	79	78	77	77	77	76	76	75	73

