

屋内照明器具特性	
品番 (品名)	NNF 2 6 9 0 6 C
光源	LED3000_70_3060 ×1 3060.0 lm
管理番号	K0171120 (0) D 1
BZ分類	BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		1 5 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		8 5 %																							
保守率		良 中 否	0 . 6 9	0 . 6	5 2	3 9	3 1	2 5	4 9	3 8	3 0	2 5	4 6	3 5	2 9	2 4	4 2	3 3	2 7	2 3	2 0				
			0 . 6 7	0 . 8	6 1	4 9	4 0	3 4	5 8	4 7	3 9	3 4	5 4	4 4	3 7	3 2	5 0	4 1	3 5	3 1	2 7				
			0 . 6 3	1 . 0	6 7	5 6	4 7	4 1	6 4	5 4	4 6	4 0	5 9	5 0	4 4	3 8	5 5	4 7	4 1	3 7	3 3				
				1 . 2 5	7 3	6 2	5 4	4 8	7 0	6 0	5 3	4 7	6 5	5 6	5 0	4 5	6 0	5 3	4 7	4 3	3 8				
下方投影面積		c m ²	1 . 5	7 7	6 7	5 9	5 3	7 4	6 5	5 8	5 2	6 8	6 1	5 5	5 0	6 3	5 7	5 2	4 7	4 3					
			等価発光面積		c m ²	2 . 0	8 3	7 4	6 7	6 1	8 0	7 2	6 5	6 0	7 4	6 7	6 2	5 7	6 8	6 3	5 8	5 4	4 9		
取付高さ	器具間隔最大限		2 . 5	8 6	7 9	7 2	6 7	8 3	7 6	7 1	6 5	7 7	7 2	6 7	6 2	7 2	6 7	6 3	5 9	5 4					
	横方向 (A)		縦方向 (B)	3 . 0	8 9	8 2	7 6	7 1	8 6	8 0	7 4	7 0	8 0	7 5	7 0	6 6	7 4	7 0	6 7	6 3	5 7				
1 . 5 m	2 . 0 7 m	2 . 0 3 m	4 . 0	9 2	8 7	8 2	7 8	8 9	8 4	8 0	7 6	8 3	7 9	7 5	7 2	7 8	7 4	7 1	6 8	6 2					
2	2 . 7 4	2 . 6 1	5 . 0	9 5	9 0	8 6	8 2	9 2	8 7	8 3	8 0	8 6	8 2	7 9	7 6	8 0	7 7	7 4	7 2	6 6					
2 . 5	3 . 4 1	3 . 2 2	7 . 0	9 7	9 4	9 0	8 7	9 4	9 1	8 8	8 5	8 8	8 6	8 3	8 1	8 3	8 1	7 8	7 6	7 0					
3	4 . 0 9	3 . 8 3	1 0 . 0	9 9	9 6	9 4	9 1	9 6	9 4	9 1	8 9	9 1	8 8	8 6	8 5	8 5	8 3	8 2	8 0	7 3					

