

屋内照明器具特性	
品番 (品名)	NNF 2 6 9 1 3 C
光源	LED4000_70_4600 ×1 4600.0 lm
管理番号	K0171119 (2) D 1
B Z 分類	BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		15 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		85 %																								
保守率		良 中 否	0.69	0.6	52	39	31	25	49	38	30	25	46	35	29	24	42	33	27	23	20					
			0.67	0.8	61	49	40	34	58	47	39	33	54	44	37	32	50	41	35	31	27					
			0.63	1.0	67	55	47	41	64	54	46	40	59	50	44	38	55	47	41	37	33					
				1.25	73	62	54	48	70	60	53	47	65	56	50	45	60	53	47	43	38					
下方投影面積		cm ²		1.5	77	67	59	53	74	65	58	52	68	61	55	50	63	57	52	47	43					
			等価発光面積		cm ²	2.0	83	74	67	61	80	72	65	60	74	67	62	57	68	63	58	54	49			
取付 高さ	器具間隔最大限		2.5	86	79	72	67	83	76	70	65	77	72	67	62	72	67	63	59	54						
	横方向 (A)		縦方向 (B)	3.0	89	82	76	71	86	80	74	70	80	75	70	66	74	70	67	63	57					
1.5m	2.09 m	2.13 m	4.0	92	87	82	78	89	84	80	76	83	79	75	72	78	74	71	68	62						
2	2.76	2.7	5.0	95	90	86	82	91	87	83	80	86	82	79	76	80	77	74	72	66						
2.5	3.43	3.28	7.0	97	94	90	87	94	91	88	85	88	86	83	81	83	81	78	76	70						
3	4.09	3.88	10.0	99	96	94	91	96	94	91	89	91	88	86	85	85	83	82	80	73						

