

屋内照明器具特性	
品番 (品名)	X A S 1 5 3 4 N
光源	L E D 5 0 0 0 _ 7 0 _ 4 4 0 × 1 4 4 0 . 0 l m
管理番号	K 0 1 7 1 2 2 0 (1) D B 1
B Z 分類	B Z 1

器具効率 上方光束 下方光束	100 % 1 % 99 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
		壁	床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		室指数		照明率 (X 0 . 0 1) Z C M																
保守率	良 0 . 6 7	0 . 6	84	78	74	71	83	77	73	71	81	76	73	71	80	76	73	71	69	
	中 0 . 6 3	0 . 8	89	84	80	78	89	83	80	77	87	83	79	77	86	82	79	77	76	
	否 0 . 5 6	1 . 0	93	88	85	82	92	88	84	82	90	86	84	81	89	85	83	81	79	
下方投影面積 等価発光面積	c m ² c m ²	1 . 2 5	96	92	88	86	95	91	88	86	93	90	87	85	91	89	86	84	83	
		1 . 5	98	94	91	89	97	93	91	88	95	92	90	88	93	91	89	87	85	
		2 . 0	100	97	95	93	99	96	94	92	97	95	93	91	95	93	92	90	88	
取付 高さ	器具間隔最大限		2 . 5	102	99	97	95	101	98	96	94	99	97	95	93	97	95	94	92	90
	横方向 (A)	縦方向 (B)	3 . 0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	94	92
	H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	104	102	101	99	103	101	100	99	101	100	98	97	99	98	97	96
				5 . 0	105	104	102	101	104	103	101	100	102	101	99	99	100	99	98	97
				7 . 0	106	105	104	103	105	104	103	102	102	101	100	100	100	99	98	96
				10 . 0	107	106	105	104	105	104	103	103	103	102	101	101	100	100	99	97

