

屋内照明器具特性	
品番 (品名)	XAS3391L
光源	LED2700_70_1035 x1 1035.0lm
管理番号	K0171366(0)D 1
BZ分類	BZ1

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		4 4 %	室指数	照明率 (X 0 . 0 1)																				Z C M
下方光束		5 6 %																						
保守率		良	0 . 6 7	0 . 6	6 7	5 9	5 4	5 0	6 3	5 7	5 2	4 9	5 7	5 2	4 9	4 7	5 2	4 8	4 6	4 4	4 0			
		中	0 . 6 3	0 . 8	7 3	6 6	6 1	5 7	6 9	6 3	5 9	5 6	6 2	5 8	5 5	5 2	5 6	5 3	5 1	4 9	4 3			
		否	0 . 5 6	1 . 0	7 8	7 1	6 6	6 3	7 3	6 8	6 4	6 0	6 6	6 2	5 9	5 6	5 9	5 6	5 4	5 2	4 6			
				1 . 2 5	8 1	7 5	7 1	6 7	7 7	7 2	6 8	6 5	6 9	6 5	6 2	6 0	6 1	5 8	5 7	5 5	4 7			
下方投影面積		c m ²	1 . 5	8 4	7 9	7 4	7 1	7 9	7 5	7 1	6 8	7 1	6 7	6 5	6 3	6 2	6 0	5 9	5 7	4 9				
			2 . 0	8 7	8 3	7 9	7 6	8 3	7 9	7 6	7 3	7 3	7 0	6 8	6 6	6 4	6 3	6 1	6 0	5 0				
取付 高さ	器具間隔最大限		2 . 5	9 0	8 6	8 3	8 0	8 4	8 1	7 9	7 6	7 5	7 2	7 1	6 9	6 6	6 4	6 3	6 2	5 1				
	横方向 (A)	縦方向 (B)	3 . 0	9 1	8 8	8 5	8 2	8 6	8 3	8 1	7 8	7 6	7 4	7 2	7 1	6 6	6 5	6 4	6 3	5 2				
H m	0 . 4 1 H m	0 . 4 1 H m	4 . 0	9 3	9 0	8 8	8 6	8 8	8 5	8 3	8 2	7 7	7 6	7 4	7 3	6 7	6 7	6 6	6 5	5 3				
			5 . 0	9 4	9 2	9 0	8 8	8 9	8 7	8 5	8 4	7 8	7 7	7 6	7 5	6 8	6 7	6 7	6 6	5 3				
			7 . 0	9 5	9 4	9 2	9 1	9 0	8 8	8 7	8 6	7 9	7 8	7 7	7 6	6 9	6 8	6 8	6 7	5 4				
			1 0 . 0	9 6	9 5	9 4	9 3	9 1	9 0	8 9	8 8	8 0	7 9	7 8	7 8	6 9	6 9	6 9	6 8	5 4				

