

屋内照明器具特性	
品番 (品名)	XAS3391N
光源	LED5000_70_1035 x1 1035.0lm
管理番号	K0171366(0)D 1
BZ分類	BZ1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		44 %	室指数	照明率 (X0.01)																				ZCM	
下方光束		56 %																							
保守率		良 中 否	0.67	0.6	67	59	54	50	63	57	52	49	57	52	49	47	52	48	46	44	40				
			0.63	0.8	73	66	61	57	69	63	59	56	62	58	55	52	56	53	51	49	43				
			0.56	1.0	78	71	66	63	73	68	64	60	66	62	59	56	59	56	54	52	46				
				1.25	81	75	71	67	77	72	68	65	69	65	62	60	61	58	57	55	47				
下方投影面積		c m ²		1.5	84	79	74	71	79	75	71	68	71	67	65	63	62	60	59	57	49				
等価発光面積			c m ²	2.0	87	83	79	76	83	79	76	73	73	70	68	66	64	63	61	60	50				
取付 高さ	器具間隔最大限		2.5	90	86	83	80	84	81	79	76	75	72	71	69	66	64	63	62	51					
	横方向 (A)		縦方向 (B)	3.0	91	88	85	82	86	83	81	78	76	74	72	71	66	65	64	63	52				
H m	0.41 H m	0.41 H m	4.0	93	90	88	86	88	85	83	82	77	76	74	73	67	67	66	65	53					
			5.0	94	92	90	88	89	87	85	84	78	77	76	75	68	67	67	66	53					
			7.0	95	94	92	91	90	88	87	86	79	78	77	76	69	68	68	67	54					
			10.0	96	95	94	93	91	90	89	88	80	79	78	78	69	69	69	68	54					

