

屋内照明器具特性	
品番 (品名)	XAS3392L
光源	LED2700_70_1340 x1 1340.0lm
管理番号	K0171370(0)D 1
BZ分類	BZ1/3.5/BZ2

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		4 2 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		5 8 %																				
保守率		良	0 . 6 7	0 . 6	6 4	5 6	5 1	4 7	6 1	5 4	4 9	4 6	5 5	5 0	4 6	4 3	5 0	4 6	4 3	4 1	3 7	
		中	0 . 6 3	0 . 8	7 1	6 3	5 8	5 4	6 7	6 0	5 6	5 2	6 0	5 5	5 2	4 9	5 4	5 0	4 8	4 5	4 0	
		否	0 . 5 6	1 . 0	7 6	6 8	6 3	5 9	7 1	6 5	6 0	5 7	6 4	5 9	5 6	5 3	5 7	5 3	5 1	4 9	4 2	
		1 . 2 5	8 0	7 3	6 8	6 4	7 5	6 9	6 5	6 1	6 7	6 3	5 9	5 7	5 9	5 6	5 4	5 2	4 4			
下方投影面積		c m ²	1 . 5	8 2	7 6	7 2	6 8	7 8	7 2	6 8	6 5	6 9	6 5	6 2	6 0	6 1	5 8	5 6	5 4	4 6		
等価発光面積			c m ²	2 . 0	8 6	8 1	7 7	7 3	8 1	7 7	7 3	7 0	7 2	6 9	6 6	6 4	6 3	6 1	5 9	5 7	4 8	
取付	器具間隔最大限		2 . 5	8 8	8 4	8 0	7 7	8 3	8 0	7 6	7 4	7 4	7 1	6 9	6 7	6 5	6 3	6 1	6 0	4 9		
高さ	横方向 (A)		縦方向 (B)	3 . 0	9 0	8 6	8 3	8 0	8 5	8 2	7 9	7 6	7 5	7 3	7 0	6 9	6 6	6 4	6 3	6 1	5 0	
H m	0 . 4 1 H m	0 . 4 1 H m		4 . 0	9 2	8 9	8 6	8 4	8 7	8 4	8 2	8 0	7 7	7 5	7 3	7 1	6 7	6 6	6 5	6 3	5 2	
			5 . 0	9 3	9 1	8 9	8 6	8 8	8 6	8 4	8 2	7 8	7 6	7 5	7 3	6 8	6 7	6 6	6 5	5 3		
			7 . 0	9 5	9 3	9 1	8 9	8 9	8 8	8 6	8 5	7 9	7 8	7 7	7 6	6 9	6 8	6 7	6 7	5 4		
			1 0 . 0	9 6	9 5	9 3	9 2	9 1	8 9	8 8	8 7	8 0	7 9	7 8	7 7	7 0	6 9	6 9	6 8	5 4		

