

|          |                              |
|----------|------------------------------|
| 屋内照明器具特性 |                              |
| 品番 (品名)  | XLX449NBN                    |
| 光源       | LED5000_85_2920 x1 2920.0 1m |
| 管理番号     | K0135074 (* ) DB 1           |
| BZ分類     | BZ5                          |

|        |                 |         |               |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     |     |     |
|--------|-----------------|---------|---------------|------|------|-----|------|------|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|-----|
| 器具効率   | 100 %           | 天井      | 80 %          |      |      |     | 70 % |      |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |     |
|        |                 | 壁       | 70            | 50   | 30   | 10  | 70   | 50   | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |     |
| 上方光束   | 4 %             | 床       | 10 %          |      |      |     | 10 % |      |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |     |
| 下方光束   | 96 %            | 室指数     | 照明率 ( X0.01 ) |      |      |     |      |      |     |     |      |     |     |     |      |     |     |     | ZCM |     |
| 保守率    | 良               | 0.83    | 0.6           | 5.6  | 4.4  | 3.6 | 3.0  | 5.4  | 4.3 | 3.6 | 3.0  | 5.2 | 4.2 | 3.5 | 3.0  | 4.9 | 4.0 | 3.4 | 3.0 | 2.7 |
|        | 中               | 0.81    | 0.8           | 6.6  | 5.4  | 4.6 | 4.1  | 6.4  | 5.3 | 4.6 | 4.0  | 6.1 | 5.1 | 4.5 | 4.0  | 5.8 | 5.0 | 4.4 | 3.9 | 3.7 |
|        | 否               | 0.77    | 1.0           | 7.2  | 6.1  | 5.4 | 4.8  | 7.0  | 6.0 | 5.3 | 4.7  | 6.7 | 5.8 | 5.2 | 4.7  | 6.4 | 5.6 | 5.1 | 4.6 | 4.3 |
|        |                 |         | 1.25          | 7.8  | 6.8  | 6.1 | 5.5  | 7.6  | 6.7 | 6.0 | 5.5  | 7.2 | 6.5 | 5.9 | 5.4  | 6.9 | 6.2 | 5.7 | 5.3 | 5.0 |
| 下方投影面積 | cm <sup>2</sup> |         | 1.5           | 8.2  | 7.3  | 6.6 | 6.0  | 8.0  | 7.2 | 6.5 | 6.0  | 7.6 | 6.9 | 6.4 | 5.9  | 7.3 | 6.7 | 6.2 | 5.8 | 5.5 |
| 等価発光面積 | cm <sup>2</sup> |         | 2.0           | 8.8  | 8.0  | 7.4 | 6.9  | 8.6  | 7.9 | 7.3 | 6.8  | 8.2 | 7.6 | 7.1 | 6.7  | 7.8 | 7.3 | 6.9 | 6.5 | 6.2 |
| 取付高さ   | 器具間隔最大限         |         | 2.5           | 9.1  | 8.5  | 7.9 | 7.4  | 8.9  | 8.3 | 7.8 | 7.3  | 8.5 | 8.0 | 7.6 | 7.2  | 8.2 | 7.7 | 7.4 | 7.0 | 6.7 |
|        | 横方向 (A)         | 縦方向 (B) | 3.0           | 9.4  | 8.8  | 8.3 | 7.8  | 9.2  | 8.6 | 8.2 | 7.8  | 8.8 | 8.3 | 7.9 | 7.6  | 8.4 | 8.1 | 7.7 | 7.4 | 7.1 |
| 1.5m   | 1.94 m          | 2.1 m   | 4.0           | 9.7  | 9.2  | 8.8 | 8.4  | 9.5  | 9.0 | 8.7 | 8.3  | 9.1 | 8.7 | 8.4 | 8.1  | 8.8 | 8.5 | 8.2 | 7.9 | 7.6 |
| 2      | 2.56            | 2.64    | 5.0           | 9.9  | 9.5  | 9.1 | 8.8  | 9.7  | 9.3 | 9.0 | 8.7  | 9.3 | 9.0 | 8.7 | 8.5  | 9.0 | 8.7 | 8.5 | 8.3 | 7.9 |
| 2.5    | 3.19            | 3.21    | 7.0           | 10.1 | 9.8  | 9.5 | 9.3  | 9.9  | 9.6 | 9.4 | 9.1  | 9.6 | 9.3 | 9.1 | 8.9  | 9.2 | 9.0 | 8.8 | 8.7 | 8.3 |
| 3      | 3.8             | 3.79    | 10.0          | 10.3 | 10.1 | 9.8 | 9.6  | 10.1 | 9.9 | 9.7 | 9.5  | 9.7 | 9.6 | 9.4 | 9.3  | 9.4 | 9.3 | 9.1 | 9.0 | 8.6 |

