

屋内照明器具特性	
品番 (品名)	NTN82420
光源	LDR3L-M-E11 x1 185.0 l m
管理番号	K0174888 (1) DR1
BZ分類	BZ1

器具効率		95 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			ZCM	
下方光束		95 %																						
保守率		良 中 否	0.67	0.6	92	89	87	86	91	89	87	86	91	88	87	86	90	88	87	85	85			
			0.63	0.8	95	92	90	89	94	92	90	89	93	91	90	89	92	91	89	88	88			
			0.56	1.0	96	94	93	91	96	94	92	91	95	93	92	91	94	92	91	90	90			
			1.25	98	96	94	93	97	95	94	93	96	95	93	92	95	94	93	92	91				
下方投影面積		c m ²	1.5	99	97	96	95	98	97	95	94	97	96	94	94	96	95	94	93	92				
			2.0	100	99	97	97	99	98	97	96	98	97	96	95	96	96	95	94	93				
等価発光面積		c m ²	2.5	100	99	97	97	99	98	97	96	98	97	96	95	96	96	95	94	93				
			3.0	101	100	99	99	100	100	99	98	99	98	98	97	97	97	96	96	95	94			
取付 高さ	器具間隔最大限		4.0	102	101	101	100	101	100	100	99	99	99	98	98	98	97	97	97	95				
	横方向 (A)		縦方向 (B)		5.0	102	101	101	101	101	101	100	100	99	99	99	98	98	97	97				
H m	0.34 H m		0.34 H m		7.0	103	102	102	102	102	101	101	101	100	100	100	99	98	98	96				
					10.0	103	103	103	103	102	102	102	102	100	100	100	98	98	98	96				

