

屋内照明器具特性	
品番 (品名)	NTN82420
光源	LDR3L-W-E11 x1 365.0 l m
管理番号	K0174895 (3) DR1
BZ分類	BZ1

器具効率		95 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		95 %	室指数	照明率 (X0.01)																		Z	C		M
下方光束																									
保守率		良	0.67	0.6	83	78	75	73	82	78	75	73	81	77	74	72	80	77	74	72	71				
		中	0.63	0.8	88	84	81	79	87	83	81	78	86	83	80	78	85	82	80	78	77				
		否	0.56	1.0	91	87	84	82	90	87	84	82	89	86	84	82	88	85	83	81	80				
				1.25	94	90	88	86	93	90	87	85	91	89	87	85	90	88	86	84	83				
下方投影面積		c m ²		1.5	95	92	90	88	94	92	89	88	93	90	89	87	91	89	88	86	85				
等価発光面積		c m ²		2.0	97	95	93	91	96	94	92	91	95	93	91	90	93	91	90	89	87				
取付 高さ	器具間隔最大限			2.5	98	96	95	93	97	96	94	93	96	94	93	92	94	93	92	91	89				
	横方向 (A)		縦方向 (B)	3.0	99	97	96	94	98	97	95	94	96	95	94	93	95	94	93	92	90				
H m	0.59 H m		0.60 H m	4.0	100	99	97	96	99	98	97	96	97	96	95	94	95	95	94	93	91				
				5.0	100	100	99	98	100	99	98	97	98	97	96	95	96	95	95	94	92				
				7.0	100	100	100	99	100	100	99	98	98	98	97	97	96	96	95	95	93				
				10.0	100	100	100	100	100	100	100	99	99	98	98	97	97	96	96	96	93				

