

屋内照明器具特性

品番 (品名)	LGB14521	
光源	LED6200_70_4578 x1 4578.0 lm	
管理番号	K0161788(0)D 1	
BZ分類	BZ5	

器具効率	100%	天井	80%				70%				50%				30%				0%				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%				
上方光束	7%	床	10%				10%				10%				10%				0%				
下方光束	93%	室指数	照明率 (X0.01)																				ZCM
保守率	良	0.67	0.6	5.6	4.4	3.6	3.1	5.4	4.3	3.5	3.0	5.1	4.1	3.5	3.0	4.8	4.0	3.4	2.9	2.7			
	中	0.63	0.8	6.6	5.4	4.6	4.1	6.4	5.3	4.6	4.0	6.0	5.1	4.4	4.0	5.7	4.9	4.3	3.9	3.6			
	否	0.56	1.0	7.2	6.1	5.4	4.8	7.0	6.0	5.3	4.8	6.6	5.8	5.2	4.7	6.3	5.6	5.0	4.6	4.3			
			1.25	7.8	6.8	6.1	5.5	7.6	6.7	6.0	5.5	7.2	6.4	5.8	5.4	6.8	6.2	5.7	5.3	4.9			
下方投影面積		cm ²	1.5	8.2	7.3	6.7	6.1	8.0	7.2	6.6	6.0	7.6	6.9	6.4	5.9	7.2	6.6	6.2	5.8	5.4			
等価発光面積		cm ²	2.0	8.8	8.1	7.4	6.9	8.6	7.9	7.3	6.9	8.1	7.6	7.1	6.7	7.8	7.3	6.9	6.5	6.2			
取付高さ	器具間隔最大限		2.5	9.1	8.5	8.0	7.5	8.9	8.3	7.9	7.4	8.5	8.0	7.6	7.2	8.1	7.7	7.4	7.0	6.7			
	横方向 (A)	縦方向 (B)	3.0	9.4	8.8	8.4	8.0	9.2	8.7	8.2	7.8	8.8	8.3	8.0	7.6	8.4	8.0	7.7	7.4	7.0			
Hm	1.24Hm	1.24Hm	4.0	9.7	9.3	8.9	8.5	9.5	9.1	8.7	8.4	9.1	8.7	8.4	8.2	8.7	8.4	8.2	7.9	7.5			
			5.0	9.9	9.5	9.2	8.9	9.7	9.3	9.0	8.8	9.3	9.0	8.7	8.5	8.9	8.7	8.5	8.3	7.8			
			7.0	10.1	9.8	9.6	9.4	9.9	9.7	9.4	9.2	9.5	9.3	9.1	8.9	9.1	9.0	8.8	8.7	8.2			
			10.0	10.3	10.1	9.9	9.7	10.1	9.9	9.7	9.6	9.7	9.5	9.4	9.3	9.3	9.2	9.1	9.0	8.5			

