

屋内照明器具特性	
品番 (品名)	NDN2 2 6 9 0
光源	LED9999_70_1605 ×1 1605.0 lm
管理番号	K0170505 (0) DB 1
B Z 分類	B Z 4

器具効率		98 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.69	0.6	60	48	41	36	58	48	41	36	56	47	41	36	54	46	40	36	34
			0.67	0.8	70	59	52	47	68	59	52	47	66	57	51	47	63	56	51	47	45
			0.63	1.0	76	67	60	55	75	66	59	55	72	64	59	54	70	63	58	54	52
			0.63	1.25	82	73	67	62	80	72	66	62	77	71	65	61	75	69	64	61	59
下方投影面積		cm ²	1.5	85	78	72	67	84	77	71	67	81	75	70	66	79	73	69	66	63	
			等価発光面積		cm ²	2.0	90	84	79	75	89	83	78	74	86	81	77	73	84	79	76
取付 高さ	器具間隔最大限		2.5	93	88	84	80	92	87	83	79	89	85	81	78	87	83	80	77	75	
	横方向 (A) 縦方向 (B)		3.0	96	91	87	83	94	90	86	83	91	88	85	82	89	86	83	81	78	
H m	1.18 H m	1.18 H m	4.0	98	95	91	88	97	93	90	88	94	91	89	86	92	89	87	85	83	
			5.0	100	97	94	92	99	96	93	91	96	94	91	89	93	92	90	88	85	
			7.0	102	99	97	95	100	98	96	95	98	96	95	93	96	94	93	91	89	
			10.0	103	102	100	99	102	100	99	98	99	98	97	96	97	96	95	94	91	

