

# 屋内照明器具特性

品番 (品名)	L G W 8 0 2 2 3 K									
光源	LED2700_70_195 ×1					195.0 l m				
管理番号	K0158606 ( 0 ) DB 1									
B Z 分類	B Z 5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																	
		床	10 %				10 %				10 %				10 %				0 %																																	
上方光束	50 %	室指数																	照明率 ( X 0.01 )																	Z C M																
下方光束	50 %																																																			
保守率	良 中 否	0.63	0.6	0.56	0.6	49	37	30	25	45	35	28	24	38	30	25	21	31	25	21	18	13																														
		0.6	0.8	58	47	39	34	53	43	37	32	45	37	32	28	37	31	27	24	18																																
		1.0	64	53	46	40	59	50	43	38	50	43	37	33	41	36	32	29	21																																	
		0.56	1.25	69	60	53	47	64	56	49	44	54	48	43	39	45	40	36	33	24																																
下方投影面積	c m <sup>2</sup>	1.5	73	65	58	52	68	60	54	49	57	51	47	43	48	43	40	37	27																																	
		2.0	79	71	65	60	73	66	61	57	62	57	53	49	51	48	45	42	31																																	
等価発光面積	c m <sup>2</sup>	2.5	82	76	70	66	76	70	66	62	64	60	57	54	54	51	48	46	34																																	
		3.0	84	79	74	70	78	73	69	65	66	63	60	57	56	53	50	48	36																																	
取付高さ	器具間隔最大限		4.0	87	83	79	75	81	77	74	71	69	66	64	61	58	56	54	40																																	
	横方向 ( A )	縦方向 ( B )																																																		
1.5 m	1.97 m	1.96 m	5.0	89	85	82	79	83	80	77	74	71	68	66	64	59	58	56	54	40																																
2	2.63	2.59	7.0	91	89	86	83	85	83	80	78	73	71	69	68	61	60	59	57	42																																
2.5	3.29	3.24	10.0	93	91	89	87	87	85	83	81	74	73	72	70	63	62	61	60	44																																
3	3.95	3.89																																																		

