

屋内照明器具特性	
品番 (品名)	NTN83324
光源	LED2700_70_350 x1 350.0 lm
管理番号	K0167962 (0) DY1
BZ分類	BZ6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		1 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		8 4 %																				
保守率		良 中 否	0 . 6 9	0 . 6	5 1	3 9	3 1	2 5	4 9	3 8	3 0	2 5	4 5	3 5	2 8	2 4	4 2	3 3	2 7	2 3	1 9	
			0 . 6 7	0 . 8	6 1	4 8	4 0	3 4	5 8	4 7	3 9	3 3	5 3	4 4	3 7	3 2	4 9	4 1	3 5	3 1	2 7	
			0 . 6 3	1 . 0	6 7	5 5	4 7	4 1	6 4	5 4	4 6	4 0	5 9	5 0	4 3	3 8	5 4	4 7	4 1	3 6	3 2	
				1 . 2 5	7 3	6 2	5 4	4 8	7 0	6 0	5 3	4 7	6 4	5 6	5 0	4 5	5 9	5 2	4 7	4 3	3 8	
下方投影面積		cm ²	1 . 5	7 7	6 7	5 9	5 3	7 4	6 5	5 8	5 2	6 8	6 1	5 4	4 9	6 3	5 7	5 1	4 7	4 2		
等価発光面積		cm ²	2 . 0	8 3	7 4	6 7	6 1	7 9	7 2	6 5	6 0	7 4	6 7	6 2	5 7	6 8	6 3	5 8	5 4	4 9		
取付 高さ	器具間隔最大限		2 . 5	8 6	7 9	7 2	6 7	8 3	7 6	7 0	6 5	7 7	7 1	6 6	6 2	7 1	6 7	6 3	5 9	5 3		
	横方向 (A)	縦方向 (B)	3 . 0	8 9	8 2	7 6	7 1	8 6	8 0	7 4	7 0	8 0	7 5	7 0	6 6	7 4	7 0	6 6	6 3	5 7		
1 . 5m	2 . 1 6 m	1 . 9 7 m	4 . 0	9 2	8 7	8 2	7 8	8 9	8 4	8 0	7 6	8 3	7 9	7 5	7 2	7 7	7 4	7 1	6 8	6 2		
2	2 . 8 6	2 . 5 5	5 . 0	9 4	9 0	8 6	8 2	9 1	8 7	8 3	8 0	8 5	8 2	7 9	7 6	8 0	7 7	7 4	7 2	6 5		
2 . 5	3 . 5 6	3 . 1 5	7 . 0	9 7	9 3	9 0	8 7	9 4	9 1	8 8	8 5	8 8	8 5	8 3	8 0	8 2	8 0	7 8	7 6	6 9		
3	4 . 2 7	3 . 7 5	1 0 . 0	9 9	9 6	9 4	9 1	9 6	9 4	9 1	8 9	9 0	8 8	8 6	8 4	8 4	8 3	8 1	8 0	7 3		

