

屋内照明器具特性	
品番 (品名)	L G W 5 6 0 0 9 B F
光源	LDA4 L - G - E17 / Z40E / S / W / 2 × 1 440.0 1 m
管理番号	K0131555 (1) DB 1
BZ分類	BZ6

器具効率	35 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	17 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	18 %		10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X0.01)																Z C M	
保守率	良	0.63	0.6	1.7	1.2	1.0	8	1.5	1.1	9	7	1.3	1.0	8	6	1.0	8	7	5	4
	中	0.6	0.8	2.0	1.6	1.3	1.1	1.8	1.4	1.2	1.0	1.5	1.2	1.0	9	1.2	1.0	9	8	5
	否	0.56	1.0	2.2	1.8	1.5	1.3	2.0	1.7	1.4	1.2	1.7	1.4	1.2	1.1	1.4	1.2	1.0	9	6
			1.25	2.4	2.0	1.8	1.5	2.2	1.9	1.6	1.5	1.8	1.6	1.4	1.3	1.5	1.3	1.2	1.1	8
下方投影面積		cm ²	1.5	2.5	2.2	1.9	1.7	2.3	2.0	1.8	1.6	1.9	1.7	1.6	1.4	1.6	1.4	1.3	1.2	9
等価発光面積		cm ²	2.0	2.7	2.4	2.2	2.0	2.5	2.2	2.0	1.9	2.1	1.9	1.8	1.6	1.7	1.6	1.5	1.4	10
取付高さ	器具間隔最大限		2.5	2.8	2.6	2.4	2.2	2.6	2.4	2.2	2.1	2.2	2.0	1.9	1.8	1.8	1.7	1.6	1.5	1.1
	横方向 (A)	縦方向 (B)	3.0	2.9	2.7	2.5	2.3	2.7	2.5	2.3	2.2	2.3	2.1	2.0	1.9	1.9	1.8	1.7	1.6	1.2
H m	1.47 H m	1.27 H m	4.0	3.0	2.8	2.7	2.5	2.8	2.6	2.5	2.4	2.4	2.3	2.2	2.1	2.0	1.9	1.8	1.8	1.3
			5.0	3.1	2.9	2.8	2.7	2.9	2.7	2.6	2.5	2.4	2.3	2.2	2.2	2.0	2.0	1.9	1.8	1.4
			7.0	3.2	3.0	2.9	2.8	2.9	2.8	2.7	2.7	2.5	2.4	2.4	2.3	2.1	2.1	2.0	2.0	1.4
			10.0	3.2	3.1	3.1	3.0	3.0	2.9	2.9	2.8	2.6	2.5	2.5	2.4	2.2	2.1	2.1	2.0	1.5

