

屋内照明器具特性	
品番 (品名)	L G W 5 6 0 0 9 S F
光源	LDA4 L - G - E17 / Z40E / S / W / 2 × 1 440.0 1 m
管理番号	K0131555 (1) DB 1
BZ分類	BZ6

器具効率	35 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	17 %	室指数	床	10 %				10 %				10 %				10 %				0 %
下方光束	18 %		照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	0.6	17	12	10	8	15	11	9	7	13	10	8	6	10	8	7	5	4
	中 0.6		0.8	20	16	13	11	18	14	12	10	15	12	10	9	12	10	9	8	5
	否 0.56		1.0	22	18	15	13	20	17	14	12	17	14	12	11	14	12	10	9	6
			1.25	24	20	18	15	22	19	16	15	18	16	14	13	15	13	12	11	8
下方投影面積	cm ²	1.5	25	22	19	17	23	20	18	16	19	17	16	14	16	14	13	12	9	
等価発光面積		2.0	27	24	22	20	25	22	20	19	21	19	18	16	17	16	15	14	10	
取付高さ		器具間隔最大限		2.5	28	26	24	22	26	24	22	21	22	20	19	18	18	17	16	11
		横方向 (A)	縦方向 (B)	3.0	29	27	25	23	27	25	23	22	23	21	20	19	19	18	17	16
H m	1.47 H m	1.27 H m	4.0	30	28	27	25	28	26	25	24	24	23	22	21	20	19	18	13	
			5.0	31	29	28	27	29	27	26	25	24	23	22	22	20	20	19	18	14
			7.0	32	30	29	28	29	28	27	27	25	24	24	23	21	21	20	20	14
			10.0	32	31	31	30	30	29	29	28	26	25	25	24	22	21	21	20	15

