

# 屋内照明器具特性

品番 (品名)	L G W 5 6 9 3 5 A Z														
光源	LDA4L-G-E17/Z40E/S/W/2 ×1										440.0 1 m				
管理番号	K0138524 (1) DR 1														
BZ分類	BZ10														

器具効率	87 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %			
上方光束	52 %	室指数	照明率 ( X0.01)															ZCM		
下方光束	35 %																			
保守率	良 中 否	0.63	0.6	37	26	19	14	33	23	17	13	26	18	13	10	19	14	10	7	2
		0.6	0.8	44	33	26	20	39	30	23	18	31	23	18	14	23	18	14	10	4
		0.56	1.0	49	39	31	25	44	35	28	23	34	28	22	18	26	21	17	14	6
			1.25	54	44	37	31	48	40	33	28	38	32	26	22	29	24	20	17	8
下方投影面積	c m <sup>2</sup>	1.5	57	48	41	35	52	44	37	32	41	35	30	26	31	26	23	20	10	
		2.0	62	54	48	42	56	49	43	39	45	40	35	31	34	30	27	24	13	
等価発光面積	c m <sup>2</sup>	2.5	65	58	53	47	59	53	48	43	48	43	39	35	37	33	30	27	15	
		3.0	68	61	56	51	61	56	51	47	50	45	42	38	38	35	32	30	17	
取付高さ	器具間隔最大限		4.0	71	66	61	57	64	60	56	52	52	49	46	43	41	38	36	33	20
	横方向 (A)	縦方向 (B)	5.0	73	68	64	61	66	62	59	56	54	51	48	46	42	40	38	36	21
H m	0.00 H m	0.00 H m	7.0	75	72	68	65	69	66	63	60	56	54	52	49	44	43	41	39	24
			10.0	77	74	72	70	71	68	66	64	58	56	54	53	46	45	43	42	26

