

屋内照明器具特性	
品番 (品名)	LGW85017Z
光源	LDA7L-G/Z60E/S/W/2 ×1 810.0 1 m
管理番号	K0157668(0)DB1
BZ分類	BZ7

器具効率	82%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	28%	床	10%				10%				10%				10%				0%	
下方光束	54%	室指数	照明率 (X0.01) ZCM																	
保守率	良 0.69 中 0.67 否 0.63	0.6	3.9	2.8	2.2	1.7	3.6	2.7	2.1	1.6	3.1	2.4	1.8	1.5	2.7	2.1	1.6	1.3	0.9	
		0.8	4.6	3.6	2.9	2.4	4.3	3.4	2.7	2.2	3.7	3.0	2.4	2.0	3.2	2.6	2.1	1.8	1.4	
		1.0	5.1	4.1	3.4	2.9	4.7	3.9	3.2	2.7	4.1	3.4	2.9	2.5	3.5	3.0	2.5	2.2	1.7	
		1.25	5.5	4.6	3.9	3.4	5.2	4.4	3.7	3.2	4.5	3.8	3.3	2.9	3.9	3.4	2.9	2.6	2.0	
下方投影面積	c m ²	1.5	5.9	5.0	4.4	3.8	5.5	4.7	4.1	3.6	4.8	4.2	3.7	3.3	4.1	3.7	3.2	2.9	2.3	
		2.0	6.3	5.6	5.0	4.5	5.9	5.3	4.7	4.3	5.2	4.7	4.2	3.8	4.5	4.1	3.7	3.4	2.7	
取付高さ	器具間隔最大限		2.5	6.6	6.0	5.4	5.0	6.2	5.7	5.1	4.7	5.5	5.0	4.6	4.2	4.8	4.4	4.1	3.8	3.0
	横方向 (A)	縦方向 (B)	3.0	6.9	6.3	5.8	5.3	6.5	5.9	5.5	5.1	5.7	5.3	4.9	4.5	5.0	4.6	4.3	4.0	3.2
H m	1.49 H m	1.48 H m	4.0	7.2	6.7	6.2	5.8	6.7	6.3	5.9	5.6	6.0	5.6	5.3	5.0	5.2	4.9	4.7	4.4	3.6
			5.0	7.3	6.9	6.5	6.2	6.9	6.5	6.2	5.9	6.1	5.8	5.6	5.3	5.4	5.1	4.9	4.7	3.8
			7.0	7.6	7.2	6.9	6.6	7.2	6.9	6.6	6.3	6.4	6.1	5.9	5.7	5.6	5.4	5.2	5.1	4.1
			10.0	7.7	7.5	7.3	7.0	7.3	7.1	6.9	6.7	6.5	6.4	6.2	6.0	5.8	5.6	5.5	5.4	4.4

