

屋内照明器具特性	
品番 (品名)	LGC31104
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0175412 (0) D 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01)																Z	CM
保守率		良 中 否	0.63	0.6	0.6	55	43	35	30	53	42	35	29	50	40	34	29	47	39	33	28	26
			0.6	0.8	65	53	45	40	63	52	45	39	59	50	43	38	56	48	42	38	35	
			0.56	1.0	71	60	53	47	69	59	52	46	65	57	50	45	61	54	49	44	41	
				1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	60	55	51	47	
下方投影面積 等価発光面積		cm ²		1.5	81	72	65	59	79	71	64	59	74	67	62	57	70	65	60	56	52	
				2.0	87	79	73	68	84	77	72	67	80	74	69	65	76	71	67	63	59	
				2.5	90	84	78	73	88	82	77	72	83	78	74	70	79	75	71	68	64	
				3.0	93	87	82	77	90	85	80	76	86	81	77	74	82	78	75	72	67	
H _m	1.24H _m		1.24H _m		4.0	96	91	87	83	93	89	85	82	89	85	82	79	85	82	79	77	72
					5.0	98	94	90	87	95	92	89	86	91	88	85	83	87	84	82	80	75
					7.0	100	97	94	92	98	95	92	90	93	91	89	87	89	87	86	84	79
					10.0	102	100	98	96	100	98	96	94	95	94	92	90	91	90	89	87	82

