

屋内照明器具特性	
品番 (品名)	LGC21104
光源	LED6200_70_3699 ×1 3699.0 lm
管理番号	K0175412 (0) D 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	0.6	55	43	35	30	53	42	35	29	50	40	34	29	47	39	33	28	26
			0.6	0.8	65	53	45	40	63	52	45	39	59	50	43	38	56	48	42	38	35	
			0.56	1.0	71	60	53	47	69	59	52	46	65	57	50	45	61	54	49	44	41	
				1.25	77	67	60	54	75	66	59	53	71	63	57	52	67	60	55	51	47	
下方投影面積 等価発光面積		cm ²		1.5	81	72	65	59	79	71	64	59	74	67	62	57	70	65	60	56	52	
				2.0	87	79	73	68	84	77	72	67	80	74	69	65	76	71	67	63	59	
				2.5	90	84	78	73	88	82	77	72	83	78	74	70	79	75	71	68	64	
				3.0	93	87	82	77	90	85	80	76	86	81	77	74	82	78	75	72	67	
Hm	1.24Hm		1.24Hm		4.0	96	91	87	83	93	89	85	82	89	85	82	79	85	82	79	77	72
			5.0	98	94	90	87	95	92	89	86	91	88	85	83	87	84	82	80	75		
			7.0	100	97	94	92	98	95	92	90	93	91	89	87	89	87	86	84	79		
			10.0	102	100	98	96	100	98	96	94	95	94	92	90	91	90	89	87	82		

