

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 3 8
光源	L L D 4 0 0 0 L C T 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 9 0 5 0 1 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4 / 2 . 3 / B Z 5

器具効率		43 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	2.4	1.9	1.6	1.4	2.4	1.9	1.6	1.4	2.3	1.9	1.6	1.4	2.2	1.8	1.5	1.4	1.3
			0.63	0.8	2.9	2.4	2.1	1.8	2.8	2.3	2.0	1.8	2.7	2.3	2.0	1.8	2.5	2.2	2.0	1.8	1.7
			0.56	1.0	3.1	2.7	2.4	2.1	3.1	2.6	2.3	2.1	2.9	2.6	2.3	2.1	2.8	2.5	2.2	2.1	1.9
				1.25	3.4	3.0	2.7	2.4	3.3	2.9	2.6	2.4	3.1	2.8	2.6	2.4	3.0	2.7	2.5	2.3	2.2
下方投影面積		cm ²	1.5	3.5	3.2	2.9	2.7	3.5	3.1	2.9	2.6	3.3	3.0	2.8	2.6	3.2	2.9	2.7	2.6	2.4	
			2.0	3.8	3.5	3.2	3.0	3.7	3.4	3.2	3.0	3.5	3.3	3.1	2.9	3.4	3.2	3.0	2.9	2.7	
等価発光面積		cm ²	2.5	3.9	3.7	3.4	3.2	3.8	3.6	3.4	3.2	3.7	3.5	3.3	3.2	3.5	3.4	3.2	3.1	3.0	
			3.0	4.0	3.8	3.6	3.4	3.9	3.7	3.5	3.4	3.8	3.6	3.5	3.3	3.6	3.5	3.4	3.2	3.1	
Hm	0.85Hm		0.85Hm	4.0	4.1	4.0	3.8	3.7	4.1	3.9	3.8	3.6	3.9	3.8	3.7	3.5	3.8	3.7	3.6	3.3	
				5.0	4.2	4.1	3.9	3.8	4.1	4.0	3.9	3.8	4.0	3.9	3.8	3.7	3.9	3.8	3.7	3.4	
				7.0	4.3	4.2	4.1	4.0	4.2	4.1	4.0	4.0	4.1	4.0	3.9	3.9	4.0	3.9	3.8	3.6	
				10.0	4.4	4.3	4.2	4.2	4.3	4.2	4.2	4.1	4.2	4.1	4.1	4.0	4.0	4.0	3.9	3.7	

