

| 屋内照明器具特性 |                          |
|----------|--------------------------|
| 品番 (品名)  | LGB16700                 |
| 光源       | LLD3020LCB1 ×1 795.0 l m |
| 管理番号     | K0176261 ( 0 ) DR 1      |
| B Z 分類   | BZ1                      |

| 器具効率   |           | 60 %             | 反射率       | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |  |  |   |   |  |   |
|--------|-----------|------------------|-----------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|--|--|---|---|--|---|
|        |           |                  |           | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |  |  |   |   |  |   |
|        |           |                  |           | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |  |  |   |   |  |   |
| 上方光束   |           | 0 %              | 室指数       | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |  |  | Z | C |  | M |
| 下方光束   |           | 60 %             |           |               |      |     |     |     |      |     |     |     |      |     |     |     |      |     |     |     |     |  |  |   |   |  |   |
| 保守率    |           | 良                | 0.67      | 0.6           | 4.9  | 4.5 | 4.2 | 4.1 | 4.9  | 4.5 | 4.2 | 4.1 | 4.8  | 4.4 | 4.2 | 4.1 | 4.7  | 4.4 | 4.2 | 4.0 | 4.0 |  |  |   |   |  |   |
|        |           | 中                | 0.63      | 0.8           | 5.3  | 4.9 | 4.7 | 4.5 | 5.2  | 4.9 | 4.7 | 4.5 | 5.1  | 4.8 | 4.6 | 4.5 | 5.0  | 4.8 | 4.6 | 4.5 | 4.4 |  |  |   |   |  |   |
|        |           | 否                | 0.56      | 1.0           | 5.5  | 5.2 | 4.9 | 4.8 | 5.4  | 5.1 | 4.9 | 4.8 | 5.3  | 5.1 | 4.9 | 4.7 | 5.2  | 5.0 | 4.9 | 4.7 | 4.6 |  |  |   |   |  |   |
|        |           | 1.25             | 5.7       | 5.4           | 5.2  | 5.0 | 5.6 | 5.4 | 5.2  | 5.0 | 5.5 | 5.3 | 5.1  | 5.0 | 5.4 | 5.2 | 5.1  | 5.0 | 4.9 |     |     |  |  |   |   |  |   |
| 下方投影面積 |           | c m <sup>2</sup> |           | 1.5           | 5.8  | 5.6 | 5.4 | 5.2 | 5.8  | 5.5 | 5.3 | 5.2 | 5.7  | 5.5 | 5.3 | 5.2 | 5.5  | 5.4 | 5.2 | 5.1 | 5.0 |  |  |   |   |  |   |
| 等価発光面積 |           | c m <sup>2</sup> |           | 2.0           | 6.0  | 5.8 | 5.6 | 5.5 | 5.9  | 5.7 | 5.6 | 5.5 | 5.8  | 5.7 | 5.5 | 5.4 | 5.7  | 5.6 | 5.4 | 5.3 | 5.2 |  |  |   |   |  |   |
| 取付高さ   | 器具間隔最大限   |                  | 2.5       | 6.1           | 5.9  | 5.8 | 5.6 | 6.0 | 5.9  | 5.7 | 5.6 | 5.9 | 5.8  | 5.7 | 5.6 | 5.8 | 5.7  | 5.6 | 5.5 | 5.4 |     |  |  |   |   |  |   |
|        | 横方向 ( A ) |                  | 縦方向 ( B ) | 3.0           | 6.2  | 6.0 | 5.9 | 5.8 | 6.1  | 6.0 | 5.8 | 5.7 | 6.0  | 5.9 | 5.8 | 5.7 | 5.9  | 5.8 | 5.7 | 5.6 | 5.5 |  |  |   |   |  |   |
| H m    | 0.49 H m  | 0.49 H m         | 4.0       | 6.3           | 6.1  | 6.0 | 5.9 | 6.2 | 6.1  | 6.0 | 5.9 | 6.1 | 6.0  | 5.9 | 5.8 | 5.9 | 5.9  | 5.8 | 5.7 | 5.6 |     |  |  |   |   |  |   |
|        |           |                  | 5.0       | 6.3           | 6.2  | 6.1 | 6.0 | 6.2 | 6.2  | 6.1 | 6.0 | 6.1 | 6.0  | 6.0 | 5.9 | 6.0 | 5.9  | 5.9 | 5.8 | 5.7 |     |  |  |   |   |  |   |
|        |           |                  | 7.0       | 6.4           | 6.3  | 6.2 | 6.2 | 6.3 | 6.2  | 6.2 | 6.1 | 6.2 | 6.1  | 6.1 | 6.0 | 6.0 | 6.0  | 6.0 | 5.9 | 5.8 |     |  |  |   |   |  |   |
|        |           |                  | 10.0      | 6.4           | 6.4  | 6.3 | 6.3 | 6.3 | 6.3  | 6.3 | 6.2 | 6.2 | 6.2  | 6.1 | 6.1 | 6.1 | 6.1  | 6.0 | 6.0 | 5.8 |     |  |  |   |   |  |   |

