

屋内照明器具特性	
品番 (品名)	L G W 8 5 0 1 4 W Z
光源	LDA4 L - H - E17 / E / S / W / 2 × 1 440.0 l m
管理番号	K0126055 (1) DB 1
BZ分類	BZ8 / 4.5 / BZ7 / 8.5 / BZ8

器具効率	70 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	27 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	43 %		10 %				10 %				10 %				10 %				0 %	
器具効率		室指数	照明率 (X0.01)																Z C M	
保守率	良	0.63	0.6	3.2	2.3	1.7	1.3	2.9	2.1	1.6	1.2	2.5	1.8	1.4	1.1	2.1	1.6	1.2	9	6
	中	0.6	0.8	3.8	2.9	2.3	1.9	3.5	2.7	2.2	1.8	3.0	2.3	1.9	1.5	2.5	2.0	1.6	13	9
	否	0.56	1.0	4.2	3.4	2.8	2.3	3.9	3.1	2.6	2.2	3.3	2.7	2.3	1.9	2.8	2.3	1.9	16	12
下方投影面積	c m ²	1.25	4.6	3.8	3.2	2.7	4.3	3.6	3.0	2.6	3.6	3.1	2.6	2.3	3.1	2.6	2.3	2.0	14	
		1.5	4.9	4.2	3.6	3.1	4.5	3.9	3.4	2.9	3.9	3.4	2.9	2.6	3.3	2.9	2.5	2.2	16	
等価発光面積	c m ²	2.0	5.3	4.7	4.1	3.7	4.9	4.4	3.9	3.5	4.2	3.8	3.4	3.1	3.6	3.2	2.9	2.7	2.0	
		2.5	5.6	5.0	4.5	4.1	5.2	4.7	4.2	3.9	4.5	4.1	3.7	3.4	3.8	3.5	3.2	3.0	2.2	
取付高さ	器具間隔最大限		3.0	5.8	5.2	4.8	4.4	5.4	4.9	4.5	4.2	4.7	4.3	4.0	3.7	4.0	3.7	3.4	3.2	2.4
	横方向 (A)	縦方向 (B)	4.0	6.0	5.6	5.2	4.9	5.6	5.2	4.9	4.6	4.9	4.6	4.3	4.0	4.2	4.0	3.7	3.5	2.7
H m	1.91 H m	1.91 H m	5.0	6.2	5.8	5.5	5.2	5.8	5.5	5.2	4.9	5.0	4.8	4.5	4.3	4.3	4.1	3.9	3.8	2.9
			7.0	6.4	6.1	5.8	5.6	6.0	5.7	5.5	5.2	5.2	5.0	4.8	4.6	4.5	4.4	4.2	4.1	3.2
			10.0	6.5	6.3	6.1	5.9	6.1	5.9	5.8	5.6	5.4	5.2	5.1	4.9	4.7	4.6	4.4	4.3	3.4

