

屋内照明器具特性	
品番(品名)	LGW85015WZ
光源	LDA4L-H-E17/E/S/W/2 ×1 440.0lm
管理番号	K0126056(1)DB1
BZ分類	BZ8/0.7/BZ7

器具効率	76%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	28%	床	10%				10%				10%				10%				0%	
下方光束	48%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.63	0.6	3.5	2.6	1.9	1.5	3.3	2.4	1.8	1.4	2.8	2.1	1.6	1.3	2.4	1.8	1.4	1.1	0.8	
	中 0.6	0.8	4.2	3.3	2.6	2.1	3.9	3.0	2.5	2.0	3.4	2.7	2.2	1.8	2.9	2.3	1.9	1.6	1.2	
	否 0.56	1.0	4.7	3.8	3.1	2.6	4.3	3.5	2.9	2.5	3.7	3.1	2.6	2.2	3.2	2.7	2.3	1.9	1.4	
		1.25	5.1	4.2	3.6	3.1	4.7	4.0	3.4	2.9	4.1	3.5	3.0	2.6	3.5	3.0	2.6	2.3	1.7	
下方投影面積	cm ²	1.5	5.4	4.6	4.0	3.5	5.0	4.3	3.8	3.3	4.4	3.8	3.3	3.0	3.7	3.3	2.9	2.6	2.0	
等価発光面積	cm ²	2.0	5.8	5.2	4.6	4.1	5.5	4.8	4.3	3.9	4.7	4.2	3.8	3.5	4.1	3.7	3.4	3.1	2.4	
取付高さ	器具間隔最大限		2.5	6.1	5.5	5.0	4.6	5.7	5.2	4.7	4.3	5.0	4.6	4.2	3.9	4.3	4.0	3.7	3.4	2.6
	横方向(A)	縦方向(B)	3.0	6.3	5.8	5.3	4.9	5.9	5.4	5.0	4.6	5.2	4.8	4.4	4.1	4.5	4.2	3.9	3.7	2.9
Hm	1.65Hm	1.65Hm	4.0	6.6	6.1	5.7	5.4	6.2	5.8	5.4	5.1	5.4	5.1	4.8	4.6	4.7	4.5	4.2	4.0	3.2
			5.0	6.8	6.4	6.0	5.7	6.4	6.0	5.7	5.4	5.6	5.3	5.1	4.8	4.9	4.7	4.5	4.3	3.4
			7.0	7.0	6.7	6.4	6.1	6.6	6.3	6.0	5.8	5.8	5.6	5.4	5.2	5.1	4.9	4.7	4.6	3.7
			10.0	7.1	6.9	6.7	6.5	6.7	6.5	6.3	6.1	6.0	5.8	5.6	5.5	5.2	5.1	5.0	4.9	3.9

