

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 0
光源	L L D 4 0 4 0 2 C Q 1 (S H U K O U) × 1 6 2 0 . 0 1 m
管理番号	K 0 1 8 4 4 3 6 (0) D R 1
B Z 分類	B Z 1

器具効率			6 9 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束			6 9 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束																							
保守率			良 中 否	0 . 6	6 0	5 7	5 4	5 3	6 0	5 6	5 4	5 3	5 9	5 6	5 4	5 2	5 8	5 5	5 4	5 2	5 2		
				0 . 8	6 3	6 0	5 8	5 6	6 3	6 0	5 8	5 6	6 2	5 9	5 7	5 6	6 1	5 9	5 7	5 6	5 5		
				1 . 0	6 5	6 2	6 0	5 9	6 5	6 2	6 0	5 8	6 4	6 1	5 9	5 8	6 3	6 1	5 9	5 8	5 7		
				0 . 5 6	1 . 2 5	6 7	6 4	6 2	6 1	6 6	6 4	6 2	6 1	6 5	6 3	6 1	6 0	6 4	6 2	6 1	6 0	5 9	
下方投影面積			c m ²	1 . 5	6 8	6 6	6 4	6 2	6 8	6 5	6 4	6 2	6 6	6 4	6 3	6 2	6 5	6 3	6 2	6 1	6 0		
				等価発光面積			c m ²	2 . 0	7 0	6 8	6 6	6 5	6 9	6 7	6 6	6 4	6 8	6 6	6 5	6 4	6 6	6 5	6 4
取付 高さ	器具間隔最大限			2 . 5	7 1	6 9	6 7	6 6	7 0	6 8	6 7	6 6	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 3		
	横方向 (A)		縦方向 (B)	3 . 0	7 1	7 0	6 9	6 7	7 1	6 9	6 8	6 7	6 9	6 8	6 7	6 6	6 8	6 7	6 6	6 5	6 3		
H m	0 . 7 6 H m		0 . 7 6 H m	4 . 0	7 2	7 1	7 0	6 9	7 1	7 0	6 9	6 8	7 0	6 9	6 8	6 7	6 8	6 8	6 7	6 6	6 5		
				5 . 0	7 3	7 2	7 1	7 0	7 2	7 1	7 0	6 9	7 0	6 9	6 9	6 8	6 9	6 8	6 8	6 7	6 5		
				7 . 0	7 3	7 3	7 2	7 1	7 2	7 2	7 1	7 0	7 1	7 0	7 0	6 9	6 9	6 9	6 8	6 8	6 6		
				1 0 . 0	7 4	7 3	7 3	7 2	7 3	7 2	7 2	7 1	7 1	7 1	7 0	7 0	7 0	6 9	6 9	6 9	6 7		

