

| 屋内照明器具特性 |                        |
|----------|------------------------|
| 品番 (品名)  | LGB16701               |
| 光源       | LLD2000CU1 ×1 566.0 lm |
| 管理番号     | K0178743 (0) DR1       |
| BZ分類     | BZ4/6.0/BZ5            |

| 器具効率     |           | 64 %            | 反射率       | 天井   | 80 %          |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |      |
|----------|-----------|-----------------|-----------|------|---------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|------|
|          |           |                 |           | 壁    | 70            | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |      |
| 上方光束     |           | 2 %             |           | 床    | 10 %          |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |      |
| 下方光束     |           | 62 %            |           | 室指数  | 照明率 ( X0.01 ) |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z CM |
| 保守率      |           | 良<br>中<br>否     | 0.67      | 0.6  | 38            | 31 | 26 | 23 | 37   | 30 | 26 | 23 | 35   | 30 | 25 | 23 | 34   | 29 | 25 | 22 | 21  |      |
|          |           |                 | 0.63      | 0.8  | 44            | 37 | 32 | 29 | 43   | 36 | 32 | 29 | 41   | 35 | 31 | 28 | 39   | 34 | 31 | 28 | 27  |      |
|          |           |                 | 1.0       | 48   | 41            | 37 | 33 | 47 | 41   | 36 | 33 | 45 | 39   | 36 | 33 | 43 | 38   | 35 | 32 | 31 |     |      |
|          |           |                 | 0.56      | 1.25 | 51            | 45 | 41 | 38 | 50   | 45 | 41 | 37 | 48   | 43 | 40 | 37 | 46   | 42 | 39 | 36 | 35  |      |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5       | 54   | 48            | 44 | 41 | 53 | 48   | 44 | 41 | 50 | 46   | 43 | 40 | 48 | 45   | 42 | 40 | 38 |     |      |
| 等価発光面積   |           | cm <sup>2</sup> | 2.0       | 57   | 53            | 49 | 46 | 56 | 52   | 48 | 46 | 54 | 50   | 47 | 45 | 52 | 49   | 46 | 44 | 42 |     |      |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5       | 59   | 55            | 52 | 49 | 58 | 54   | 51 | 49 | 56 | 53   | 50 | 48 | 54 | 51   | 49 | 47 | 45 |     |      |
|          | 横方向 ( A ) |                 | 縦方向 ( B ) |      | 3.0           | 61 | 57 | 54 | 52   | 59 | 56 | 54 | 51   | 57 | 55 | 52 | 50   | 55 | 53 | 51 | 50  | 48   |
| H m      | 0.96 H m  |                 | 0.96 H m  |      | 4.0           | 62 | 60 | 57 | 55   | 61 | 59 | 57 | 55   | 59 | 57 | 55 | 54   | 57 | 56 | 54 | 53  | 51   |
|          |           |                 |           |      | 5.0           | 64 | 61 | 59 | 58   | 63 | 61 | 59 | 57   | 61 | 59 | 57 | 56   | 59 | 57 | 56 | 55  | 53   |
|          |           |                 |           |      | 7.0           | 65 | 63 | 62 | 60   | 64 | 62 | 61 | 60   | 62 | 61 | 59 | 58   | 60 | 59 | 58 | 57  | 55   |
|          |           |                 |           |      | 10.0          | 66 | 65 | 64 | 63   | 65 | 64 | 63 | 62   | 63 | 62 | 61 | 60   | 61 | 60 | 60 | 59  | 57   |

