

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 1
光源	L L D 4 0 4 0 2 C Q 1 (K A K U S A N) × 1 8 6 0 . 0 1 m
管理番号	K 0 1 8 4 4 3 7 (0) D R 1
B Z 分類	B Z 3 / 1 . 4 / B Z 4

器具効率		4 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		2 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		3 8 %																				
保守率		良 中 否	0 . 6 7	0 . 6	2 4	2 0	1 7	1 6	2 4	2 0	1 7	1 6	2 3	1 9	1 7	1 5	2 2	1 9	1 7	1 5	1 5	
			0 . 6 3	0 . 8	2 8	2 4	2 1	1 9	2 7	2 4	2 1	1 9	2 6	2 3	2 1	1 9	2 5	2 2	2 0	1 9	1 8	
			0 . 5 6	1 . 0	3 0	2 7	2 4	2 2	3 0	2 6	2 4	2 2	2 8	2 6	2 3	2 2	2 7	2 5	2 3	2 1	2 0	
			1 . 2 5	3 2	2 9	2 7	2 5	3 2	2 9	2 6	2 4	3 0	2 8	2 6	2 4	2 9	2 7	2 5	2 4	2 3		
下方投影面積		c m ²	1 . 5	3 4	3 1	2 8	2 6	3 3	3 0	2 8	2 6	3 2	2 9	2 8	2 6	3 1	2 9	2 7	2 6	2 5		
等価発光面積		c m ²	2 . 0	3 6	3 3	3 1	2 9	3 5	3 3	3 1	2 9	3 4	3 2	3 0	2 9	3 3	3 1	2 9	2 8	2 7		
取付 高さ	器具間隔最大限		2 . 5	3 7	3 5	3 3	3 1	3 6	3 4	3 3	3 1	3 5	3 3	3 2	3 0	3 4	3 2	3 1	3 0	2 9		
	横方向 (A)		縦方向 (B)		3 . 0	3 8	3 6	3 4	3 3	3 7	3 5	3 4	3 2	3 6	3 4	3 3	3 2	3 5	3 3	3 2	3 1	3 0
H m	0 . 9 5 H m	0 . 9 5 H m	4 . 0	3 9	3 7	3 6	3 5	3 8	3 7	3 6	3 4	3 7	3 6	3 5	3 4	3 6	3 5	3 4	3 3	3 2		
			5 . 0	4 0	3 8	3 7	3 6	3 9	3 8	3 7	3 6	3 8	3 7	3 6	3 5	3 6	3 6	3 5	3 4	3 3		
			7 . 0	4 0	3 9	3 8	3 8	4 0	3 9	3 8	3 7	3 8	3 8	3 7	3 6	3 7	3 7	3 6	3 5	3 4		
			1 0 . 0	4 1	4 0	3 9	3 9	4 0	4 0	3 9	3 8	3 9	3 8	3 8	3 7	3 8	3 7	3 7	3 7	3 5		

