

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 0 1
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 8 6 4 8 5 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4 / 2 . 3 / B Z 5

器具効率		5 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 7	0 . 6	3 1	2 5	2 1	1 8	3 1	2 5	2 1	1 8	2 9	2 4	2 0	1 8	2 8	2 3	2 0	1 8	1 6	
			0 . 6 3	0 . 8	3 7	3 1	2 6	2 3	3 6	3 0	2 6	2 3	3 4	2 9	2 6	2 3	3 3	2 8	2 5	2 3	2 1	
			0 . 5 6	1 . 0	4 0	3 5	3 0	2 7	3 9	3 4	3 0	2 7	3 7	3 3	3 0	2 7	3 6	3 2	2 9	2 7	2 5	
				1 . 2 5	4 3	3 8	3 4	3 1	4 2	3 8	3 4	3 1	4 0	3 6	3 3	3 1	3 9	3 5	3 3	3 0	2 9	
下方投影面積		c m ²	1 . 5	4 6	4 1	3 7	3 4	4 5	4 0	3 7	3 4	4 3	3 9	3 6	3 4	4 1	3 8	3 5	3 3	3 1		
			2 . 0	4 9	4 5	4 1	3 9	4 7	4 4	4 1	3 8	4 6	4 2	4 0	3 8	4 4	4 1	3 9	3 7	3 5		
取付 高さ	器具間隔最大限		2 . 5	5 0	4 7	4 4	4 2	4 9	4 6	4 4	4 1	4 7	4 5	4 3	4 1	4 6	4 3	4 1	4 0	3 8		
	横方向 (A) 縦方向 (B)		3 . 0	5 2	4 9	4 6	4 4	5 1	4 8	4 6	4 4	4 9	4 6	4 4	4 3	4 7	4 5	4 3	4 2	4 0		
H m	0 . 8 5 H m	0 . 8 5 H m	4 . 0	5 3	5 1	4 9	4 7	5 2	5 0	4 8	4 7	5 0	4 9	4 7	4 6	4 9	4 7	4 6	4 5	4 3		
			5 . 0	5 4	5 2	5 1	4 9	5 3	5 2	5 0	4 8	5 1	5 0	4 9	4 7	5 0	4 8	4 7	4 6	4 4		
			7 . 0	5 5	5 4	5 3	5 1	5 5	5 3	5 2	5 1	5 3	5 2	5 1	5 0	5 1	5 0	4 9	4 8	4 6		
			1 0 . 0	5 6	5 5	5 4	5 3	5 5	5 4	5 4	5 3	5 4	5 3	5 2	5 1	5 2	5 1	5 1	5 0	4 8		

