

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | L G B 1 5 1 0 6         |
| 光源       | LLD4000LCE1 ×1 845.0 lm |
| 管理番号     | K0176189 ( 0 ) DR 1     |
| B Z 分類   | BZ5                     |

| 器具効率     |           | 71 %            | 反射率  | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |   |   |
|----------|-----------|-----------------|------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|---|---|
|          |           |                 |      | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |   |
|          |           |                 |      | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |   |   |
| 上方光束     |           | 4 %             | 室指数  | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z | C | M |
| 下方光束     |           | 67 %            |      |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |   |   |   |
| 保守率      |           | 良<br>中<br>否     | 0.67 | 0.6           | 39   | 30 | 25 | 21 | 38   | 30 | 24 | 21 | 36   | 29 | 24 | 20 | 34   | 28 | 23 | 20 | 18  |   |   |   |
|          |           |                 | 0.63 | 0.8           | 46   | 38 | 32 | 28 | 45   | 37 | 31 | 28 | 42   | 36 | 31 | 27 | 40   | 34 | 30 | 27 | 25  |   |   |   |
|          |           |                 | 0.56 | 1.0           | 51   | 43 | 37 | 33 | 49   | 42 | 37 | 33 | 47   | 40 | 36 | 32 | 44   | 39 | 35 | 31 | 29  |   |   |   |
|          |           |                 |      | 1.25          | 55   | 48 | 42 | 38 | 53   | 47 | 42 | 38 | 51   | 45 | 41 | 37 | 48   | 43 | 39 | 36 | 34  |   |   |   |
| 下方投影面積   |           | cm <sup>2</sup> | 1.5  | 58            | 51   | 46 | 42 | 56 | 50   | 45 | 42 | 53 | 48   | 44 | 41 | 51 | 47   | 43 | 40 | 38 |     |   |   |   |
| 等価発光面積   |           | cm <sup>2</sup> | 2.0  | 62            | 56   | 52 | 48 | 60 | 55   | 51 | 48 | 57 | 53   | 50 | 46 | 55 | 51   | 48 | 45 | 43 |     |   |   |   |
| 取付<br>高さ | 器具間隔最大限   |                 | 2.5  | 64            | 60   | 56 | 52 | 63 | 59   | 55 | 52 | 60 | 56   | 53 | 50 | 57 | 54   | 52 | 49 | 47 |     |   |   |   |
|          | 横方向 ( A ) | 縦方向 ( B )       | 3.0  | 66            | 62   | 58 | 55 | 65 | 61   | 58 | 55 | 62 | 59   | 56 | 53 | 59 | 57   | 54 | 52 | 49 |     |   |   |   |
| H m      | 1.17 H m  | 1.17 H m        | 4.0  | 68            | 65   | 62 | 60 | 67 | 64   | 61 | 59 | 64 | 62   | 59 | 57 | 62 | 60   | 58 | 56 | 53 |     |   |   |   |
|          |           |                 | 5.0  | 70            | 67   | 65 | 62 | 68 | 66   | 64 | 62 | 66 | 64   | 62 | 60 | 63 | 61   | 60 | 58 | 55 |     |   |   |   |
|          |           |                 | 7.0  | 72            | 69   | 68 | 66 | 70 | 68   | 66 | 65 | 68 | 66   | 64 | 63 | 65 | 64   | 62 | 61 | 58 |     |   |   |   |
|          |           |                 | 10.0 | 73            | 71   | 70 | 69 | 71 | 70   | 69 | 67 | 69 | 68   | 67 | 66 | 66 | 65   | 65 | 64 | 61 |     |   |   |   |

