

屋内照明器具特性

品番 (品名)	NNF 4 1 8 8 5									
光源	LED_READING5000_85_1710 ×1 1710.0 1m									
管理番号	K0157495 (0) DB 1									
BZ分類	BZ5									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束	0 %	反射率	床	10 %				10 %				10 %				10 %				0 %
下方光束	100 %		室指数	照明率 (X0.01)																ZCM
保守率	良	0.83	0.6	5.5	4.2	3.4	2.8	5.3	4.1	3.4	2.8	5.1	4.0	3.3	2.8	4.9	3.9	3.3	2.8	2.6
	中	0.81	0.8	6.6	5.4	4.6	4.0	6.4	5.3	4.5	3.9	6.1	5.1	4.5	3.9	5.9	5.0	4.4	3.9	3.7
	否	0.77	1.0	7.3	6.2	5.4	4.8	7.1	6.1	5.3	4.8	6.8	5.9	5.3	4.7	6.5	5.8	5.2	4.7	4.5
			1.25	7.9	6.9	6.2	5.6	7.7	6.8	6.1	5.6	7.4	6.6	6.0	5.5	7.1	6.5	5.9	5.5	5.3
下方投影面積	c m ²		1.5	8.3	7.4	6.8	6.2	8.2	7.3	6.7	6.2	7.9	7.2	6.6	6.1	7.6	7.0	6.5	6.1	5.8
等価発光面積	c m ²		2.0	8.9	8.2	7.6	7.1	8.8	8.1	7.5	7.0	8.5	7.9	7.4	7.0	8.2	7.7	7.3	6.9	6.6
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.1	7.7	9.1	8.6	8.1	7.6	8.8	8.3	7.9	7.5	8.6	8.1	7.8	7.4	7.2
	横方向 (A)	縦方向 (B)	3.0	9.5	9.0	8.5	8.1	9.4	8.9	8.5	8.1	9.1	8.7	8.3	8.0	8.8	8.5	8.1	7.9	7.6
1.5m	1.63m	2.14m	4.0	9.9	9.4	9.1	8.7	9.7	9.3	9.0	8.6	9.4	9.1	8.8	8.5	9.2	8.9	8.6	8.4	8.1
2	2.17	2.76	5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.0	9.6	9.4	9.1	8.9	9.4	9.1	8.9	8.7	8.5
2.5	2.7	3.39	7.0	10.3	10.0	9.8	9.5	10.1	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.6	9.5	9.3	9.1	8.9
3	3.23	4.04	10.0	10.4	10.3	10.1	9.9	10.3	10.1	10.0	9.8	10.1	9.9	9.8	9.6	9.8	9.7	9.6	9.5	9.2

