

屋内照明器具特性	
品番 (品名)	LGB15106
光源	LLD2020CU1 ×1 468.0 lm
管理番号	K0179031 (0) DR1
BZ分類	BZ1 / 4.5 / BZ2

器具効率		8 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 %	室指数	照明率 (X 0 . 0 1) Z C M																			
下方光束		8 5 %																					
保守率		良 中 否	0 . 6	6 7	6 1	5 7	5 4	6 6	6 1	5 7	5 4	6 5	6 0	5 7	5 4	6 4	5 9	5 6	5 4	5 3			
			0 . 6 3	0 . 8	7 3	6 7	6 3	6 0	7 2	6 6	6 3	6 0	7 0	6 6	6 2	6 0	6 9	6 5	6 2	6 0	5 8		
			1 . 0	7 6	7 1	6 7	6 4	7 5	7 0	6 7	6 4	7 3	6 9	6 6	6 4	7 2	6 8	6 5	6 3	6 2			
			0 . 5 6	1 . 2 5	7 9	7 4	7 1	6 8	7 8	7 4	7 0	6 8	7 6	7 2	7 0	6 7	7 4	7 1	6 9	6 7	6 5		
下方投影面積		c m ²	1 . 5	8 1	7 7	7 3	7 1	8 0	7 6	7 3	7 1	7 8	7 5	7 2	7 0	7 6	7 3	7 1	6 9	6 8			
			等価発光面積		c m ²	2 . 0	8 4	8 0	7 7	7 5	8 3	7 9	7 7	7 4	8 1	7 8	7 6	7 4	7 9	7 6	7 4	7 3	7 1
取付 高さ	器具間隔最大限					2 . 5	8 5	8 2	8 0	7 7	8 4	8 1	7 9	7 7	8 2	8 0	7 8	7 6	8 0	7 8	7 7	7 5	7 3
		横方向 (A)	縦方向 (B)	3 . 0	8 6	8 4	8 1	7 9	8 5	8 3	8 1	7 9	8 3	8 1	7 9	7 8	8 1	8 0	7 8	7 7	7 5		
H m	0 . 4 0 H m	0 . 4 0 H m	4 . 0	8 8	8 6	8 4	8 2	8 7	8 5	8 3	8 1	8 5	8 3	8 1	8 0	8 3	8 1	8 0	7 9	7 7			
			5 . 0	8 9	8 7	8 5	8 4	8 8	8 6	8 4	8 3	8 5	8 4	8 3	8 2	8 3	8 2	8 1	8 0	7 8			
			7 . 0	9 0	8 8	8 7	8 6	8 9	8 7	8 6	8 5	8 6	8 5	8 4	8 4	8 4	8 4	8 3	8 2	8 0			
			1 0 . 0	9 0	8 9	8 9	8 8	8 9	8 8	8 8	8 7	8 7	8 6	8 6	8 5	8 5	8 5	8 4	8 3	8 1			

